Sony α 7C MILC Body 24.2 MP CMOS 6000 x 4000 pixels Black, Silver



Light metering *

Auto Exposure (AE) lock

Number of measurement zones

Product family: α

Product code: ILCE7CS.CEC

Product name : 7C

24.2 MP, Exmor R CMOS, E-mount, 4K, SD, 2.95" TFT, USB C, Bluetooth, 3.5mm, Wi-Fi, 124x71.1x59.7 mm. silver

Sony α 7C. Camera type: MILC Body, Megapixel (approx.): 24.2 MP, Sensor type: CMOS, Maximum image resolution: 6000 x 4000 pixels. ISO sensitivity (max): 204800. Fastest camera shutter speed: 1/4000 s. Wi-Fi. HD type: 4K Ultra HD, Maximum video resolution: 3840 x 2160 pixels. Display diagonal: 7.49 cm (2.95"), Touchscreen. Viewfinder type: Electronic. Weight: 424 g. Product colour: Black, Silver

Picture quality Memory MILC Body Compatible memory cards * SD, SDHC, SDXC Camera type * Megapixel (approx.) * 24.2 MP Display Sensor type * CMOS Display * TFT 6000 x 4000 pixels Maximum image resolution * Touchscreen * 6000 x 4000, 3936 x 2624, 3008 x 7.49 cm (2.95") Display diagonal * 2000, 3936 x 2624, 3008 x 2000, 921600 dot 1968 x 1312, 5328 x 4000, 3488 x **Display resolution** 2624, 2656 x 2000, 3488 x 2624, Flip-out screen 2656 x 2000, 1744 x 1312, 6000 x Still image resolution(s) * Vari-angle LCD display 1 3376, 3936 x 2216, 3008 x 1688, 3936 x 2216, 3008 x 1688, 1968 x Viewfinder 1112, 4000 x 4000, 2624 x 2624, 2000 x 2000, 2624 x 2624, 2000 x Viewfinder type Electronic 2000, 1312 x 1312 Magnification 0.59x Image stabilizer * 0.39" Viewfinder screen size Supported aspect ratios 3:2 Ports & interfaces Total megapixels 25.3 MP USB version * 3.2 Gen 1 (3.1 Gen 1) Image sensor size (W x H) 35.6 x 23.8 mm USB connector USB Type-C Sensor format Full-frame Microphone in 1 Image formats supported * JPEG, RAW Headphone outputs 1 Lens system 3.5 mm Headphone connectivity Lens mount interface E mount Network Focusing Bluetooth * 1 Focus adjustment * Auto/Manual Bluetooth version 4.1 Continuous Auto Focus, Contrast Wi-Fi * Auto focusing (AF) modes * Detection Auto Focus, Single Auto Near Field Communication (NFC) * ∢ Focus Auto Focus (AF) object detection Face Camera 693 Auto Focus (AF) points Auto, Cloudy, Custom modes, White balance * Auto Focus (AF) lock Daylight, Flash, Fluorescent, Incandescent, Shade, Underwater Auto Focus (AF) assist beam 1 Scene modes * Landscape, Night, Sunset Exposure Shooting modes * Auto ISO sensitivity (min) * 100 Black&White, Neutral, Sepia, Vivid Photo effects * ISO sensitivity (max) * 204800 Self-timer delay * 2,5,10 s 100, 12800, 51200, 102400, Brightness adjustment ISO sensitivity J 204800 Histogram 1 Aperture priority AE, Auto, Manual, Light exposure modes * DPOF, Exif, PRINT Image Matching Shutter priority AE Camera file system ш Light exposure control Program AE Anti-dust function 1 Light exposure correction * ± 5EV (1/2EV; 1/3EV step)

Centre-weighted, Evaluative (Multi-

pattern), Highlight-weighted, Spot

1200



Smartphone remote support

Tripod mounting supported *

View on smartphone

Image processor

1

1

7

BIONZ X

Shutter		Design	
Fastest camera shutter speed *	1/4000 s	Product colour *	Black, Silver
Slowest camera shutter speed * Camera shutter type	30 s Electronic, Mechanical	Battery	
		Battery voltage	7.2 V
Flash		Battery life (CIPA standard)	740 shots
Flash modes *	Auto, Fill-in, Flash off, Hi-speed sync, Red-eye reduction, Slow synchronization 1/160 s ✓ ±3EV (1/2; 1/3 EV step) Wireless triggering	Battery capacity	2280 mAh
		Battery type	NP-FZ100
Flash sync-speed		Number of batteries supported	1
Flash exposure compensation		Battery level indicator	1
Flash exposure correction		Charging indicator	1
Flash metering modes		Operational conditions	
Pre-flash	4	Operating temperature (T-T)	0 - 40 °C
Shoe mounting point	punting point 🗸	Weight & dimensions	
Video		Width	124 mm
Video recording *	1	Depth	59.7 mm
Maximum video resolution *	3840 x 2160 pixels	Height	71.1 mm
HD type *	4K Ultra HD	Weight	424 g
Video resolutions	1920 x 1080,3840 x 2160 pixels	Weight (including battery)	590 g
Analog signal format system Video formats supported	NTSC, PAL AVC, H.264, MPEG4, XAVC S	Packaging data	
		Quantity per pack	1 pc(s)
Audio		Packaging content	
Built-in microphone *	4	Lens cap included	1
Built-in speaker(s)			•
Audio system	stereo		

Audio formats supported

Noise reduction

LPCM

∢



4548736121669

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.