



D-Link DXS-1210-28T network switch Managed L2/L3 10G Ethernet (100/1000/10000) 1U Black

Brand : D-Link

Product code: DXS-1210-28T

Product name : DXS-1210-28T



- Access Control List
- IP-MAC-Port Binding
- Clientless MAC/Web Access Control
- D-Link Safeguard Engine
- Port Security
- ARP Spoofing Prevention

DXS-1210-28T - 24 x 10GBASE-T, 4 x 10/25G SFP28

D-Link DXS-1210-28T. Switch type: Managed, Switch layer: L2/L3. Basic switching RJ-45 Ethernet ports type: 10G Ethernet (100/1000/10000), Basic switching RJ-45 Ethernet ports quantity: 24, Console port: RJ-45. MAC address table: 32000 entries, Switching capacity: 680 Gbit/s. Networking standards: IEEE 802.3ab, IEEE 802.3ae, IEEE 802.3an, IEEE 802.3az, IEEE 802.3u, IEEE 802.3z. Rack mounting, Form factor: 1U

Management features		Security	
Switch type *	Managed	Access Control List (ACL) rules	256
Switch layer	L2/L3	IGMP snooping	✓
Quality of Service (QoS) support	✓	Protocols	
Web-based management	✓	Management protocols	SNMP v1/v2c/v3
Ports & interfaces		GARP VLAN Registration Protocol (GVRP)	✓
Basic switching RJ-45 Ethernet ports quantity *	24	Design	
Basic switching RJ-45 Ethernet ports type *	10G Ethernet (100/1000/10000)	Rack mounting *	✓
10G Ethernet (copper) ports quantity	24	Form factor	1U
Console port	RJ-45	Product colour	Black
SFP28 ports quantity	4	LED indicators	Activity, Link, Speed
Network		Number of fans	2 fan(s)
Networking standards *	IEEE 802.3ab, IEEE 802.3ae, IEEE 802.3an, IEEE 802.3az, IEEE 802.3u, IEEE 802.3z	Certification	CE Class A FCC Class A VCCI Class A IC BSMI
Cable types supported	Cat6, Cat6a, Cat7	Performance	
Port mirroring	✓	Noise level	51.9 dB
Flow control support	✓	Power	
Link aggregation	✓	AC input voltage	100 - 240 V
Auto MDI/MDI-X	✓	Power consumption (max)	87.3 W
Spanning tree protocol	✓	Power over Ethernet (PoE)	
VLAN support	✓	Power over Ethernet (PoE) *	✗
Number of VLANs	4094	Operational conditions	
Data transmission		Operating temperature (T-T)	-5 - 50 °C
Switching capacity *	680 Gbit/s	Storage temperature (T-T)	-20 - 70 °C
Forwarding rate	505.92 Mpps	Operating relative humidity (H-H)	0 - 95%
MAC address table *	32000 entries	Storage relative humidity (H-H)	0 - 95%
Store-and-forward	✓	Weight & dimensions	
Jumbo frames support	✓	Width	441 mm
Jumbo frames	9000	Depth	209.5 mm
Security		Height	44 mm
Access Control List (ACL)	✓	Weight	3.07 kg
		Logistics data	
		Harmonized System (HS) code	85176990



0790069456800



790069456800

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.