

BenQ PD2500Q computer monitor 63.5 cm (25") 2560 x 1440 pixels 2K Ultra HD LCD Grey

Brand : BenQ Product code: 9H.LG8LA.TPE

Product name: PD2500Q

- 25" 2K QHD 16:9 IPS LED Monitor
- 100% sRGB and Rec. 709
- Specialized Modes: Darkroom, CAD/CAM, and Animation modes

25" 2560x1440 IPS, 350cd/m², 1000:1, 4ms, 60Hz, 117ppi, 2x 2W, HDMI, DP, MiniDP, 4x USB 3.1 BenQ PD2500Q. Display diagonal: 63.5 cm (25"), Display resolution: 2560 x 1440 pixels, HD type: 2K Ultra HD, Display technology: LCD, Response time: 4 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). Built-in USB hub, USB hub version: 3.2 Gen 1 (3.1 Gen 1). VESA mounting, Height adjustment. Product colour: Grey











Display		Ergonomics	
Display diagonal * Display resolution * HD type * Native aspect ratio * Display technology * Panel type * Backlight type Touchscreen * Display brightness (typical) Response time	63.5 cm (25") 2560 x 1440 pixels 2K Ultra HD 16:9 LCD IPS LED 350 cd/m² 4 ms	Panel mounting interface Cable lock slot * Cable lock slot type Height adjustment * Height adjustment Pivot Pivot angle Swivelling Swivel angle range Tilt angle range	100 x 100 mm ✓ Kensington ✓ 13 cm ✓ 0 - 90° ✓ -45 - 45° -5 - 20°
Anti-glare screen Screen shape * Contrast ratio (typical) * Maximum refresh rate * Viewing angle, horizontal	Flat 1000:1 60 Hz 178° 178° 16.78 million colours 0.216 x 0.216 mm 117 ppi 63 cm sRGB 100%	On Screen Display (OSD) Number of OSD languages Tilt adjustment Power Energy efficiency class (SDR) *	√ 18 ✓
Viewing angle, vertical Display number of colours * Pixel pitch Pixel density Display diagonal (metric) RGB colour space sRGB coverage (typical)		Energy consumption (SDR) per 100 hours * Power consumption (typical) * Power consumption (standby) * Power consumption (max) Power consumption (off) AC input voltage	
Performance		Energy efficiency scale	A to G
NVIDIA G-SYNC * AMD FreeSync * Flicker-free technology Low Blue Light technology	× × •	Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	5 - 40 °C -20 - 60 °C 20 - 90% 10 - 90%

Multimedia		Packaging content	
Built-in speaker(s) * Built-in camera *		Stand included Cables included	✓ AC, HDMI, USB
Number of speakers RMS rated power	2 4 W	Weight & dimensions Width (with stand)	570.2 mm
Design		Depth (with stand)	239.7 mm
Market positioning * Product colour * Certification	Graphics design Grey TUV GS, CE, ISO9241-307	Height (with stand) Weight (with stand) Width (without stand)	532 mm 9.2 kg 570.2 mm
Ports & interfaces		Depth (without stand)	58.8 mm 359.5 mm
Built-in USB hub * USB hub version	✓ 3.2 Gen 1 (3.1 Gen 1)	Height (without stand) Weight (without stand)	7.2 kg
Number of upstream ports	1	Packaging data	
USB Type-A downstream ports quantity HDMI *	4	Package width Package depth Package height	590 mm 640 mm 165 mm
HDMI ports quantity 1 HDMI version 1.	1.4	Package Height Package weight Package type	9.2 kg Box
DisplayPorts quantity DisplayPort version	1 1.2	Sustainability	
Mini DisplayPorts quantity Headphone out *	1	Sustainability compliance Sustainability certificates	✓ ENERGY STAR, EPEAT Gold
HDCP	✓	Logistics data	
AC (power) in	✓	Harmonized System (HS) code	85285210
Ergonomics			
VESA mounting *	✓		

