

## Benq MW826STH data projector Short throw projector 3500 ANSI lumens DLP WXGA (1280x800) 3D White

Brand : Benq Product code: 9H.JMW77.13E

**Product name: MW826STH** 

- 0.49 Short Throw Ratio
- SmartEco Power Saving Technology
- PointWrite Interactive Solution Compatible

DLP, 3500 ANSI Lumen, 1280 x 800, 16:10, 20000:1, RMS 10W

Benq MW826STH. Projector brightness: 3500 ANSI lumens, Projection technology: DLP, Projector native resolution: WXGA (1280x800). Light source type: Lamp, Service life of light source: 6000 h, Service life of light source (economic mode): 10000 h. Throw ratio: 0.49:1, Offset: 105%. Supported 3D formats: Frame Sequential, Frame packing, Side by side, Top and bottom, Supported graphics resolutions: 640 x 480 (VGA), 1920 x 1200 (WUXGA), Supported video modes: 480i, 480p, 576i, 576p, 720p, 1080i, 1080p. Serial interface type: RS-232





Projector       Network         Screen size compatibility*       1778 - 3048 mm (70 - 120")       Ethernet LAN (RJ-45) ports       1         Projector brightness *       3500 ANSI lumens       Storage         Projection technology *       DLP       Card reader integrated *       X         Projector native resolution *       WXGA (1280x800)       Features       X         Contrast ratio (typical) *       20000:1       Features       ✓         Native aspect ratio *       16:10       Interactive *       ✓         Number of colours       1.07 billion colours       Noise level (economic mode)       29 dB         Keystone correction, vertical       -30 - 30°       On Screen Display (OSD)       ✓         Matrix size       1.65 cm (0.65")       Arabic, Bulgarian, Simplified Chinese, Traditional Chinese, Croatian, Czech, Danish, Germe Dutch, English, Spanish, Finnish Germe Dutch, English, Spanish, Finnish Finnish Germe Dutch, English, Spanish, Finnish French, Greek, Hindi, Hungaria Indonesian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Romanian, Russian Swedish, Thai, Turkish         Service life of light source (economic mode)       1 lamp(s)         Lamps quantity       1 lamp(s)         Lens system       V         Zoom capability       Multimedia         Throw ratio       0.49:1       Multimedia
Projector brightness * 3500 ANSI lumens Projection technology * DLP Projector native resolution * WXGA (1280x800)  Contrast ratio (typical) * 20000:1  Native aspect ratio * 16:10  Number of colours  Keystone correction, vertical  Adaptive size  Light source  Light source  Light source type *  Service life of light source (economic mode)  Service life of light source (economic mode)  Lamps quantity  Lamp (3000 h  Description of light source (economic mode)  Light source  Light source  Lamp (5000 h  Description of light source)  Noise level (economic mode)  Arabic, Bulgarian, Simplified Chinese, Traditional Chinese, Croatian, Czech, Danish, Germ Dutch, English, Spanish, Finnish French, Greek, Hindi, Hungaria Indonesian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Romanian, Russian Swedish, Thai, Turkish  Noise level *  Multimedia  Description of light source (2000 h)  Noise level *  Multimedia
Projection technology * DLP Projector native resolution * WXGA (1280x800)  Contrast ratio (typical) * 20000:1  Native aspect ratio * 16:10  Number of colours  Keystone correction, vertical  Light source  Light source  Light source type * Lamp  Service life of light source  Service life of light source  Lamps quantity  Light source  Light source  Light source  Light source  Light source   10000 h    Lamps quantity  Light source  Light source  Light source  Light source   10000 h    Lamps quantity  Noise level (economic mode)  Light source   10000 h    Noise level * 33 dB  Multimedia
Projector native resolution * WXGA (1280x800)  Contrast ratio (typical) * 20000:1  Native aspect ratio * 16:10  Number of colours 1.07 billion colours 1.07 billion colours 1.05 cm (0.65")  Matrix size 1.65 cm (0.65")  Light source Light source type * Lamp Service life of light source * Geconomic mode)  Service life of light source (economic mode)  Lamps quantity 1 lamp(s)  Lens system  Zoom capability  Card reader integrated *    Analot. Card reader integrated *    Analot. All read integrated integra
Features         Native aspect ratio *       16:10       Interactive *       ✓         Number of colours       1.07 billion colours       Noise level (economic mode)       29 dB         Keystone correction, vertical       -30 - 30°       On Screen Display (OSD)       ✓         Matrix size       1.65 cm (0.65")       Arabic, Bulgarian, Simplified Chinese, Traditional Chinese, Traditional Chinese, Croatian, Czech, Danish, Germ.         Light source       Lamp       Dutch, English, Spanish, Finnish Spanish, Finnish French, Greek, Hindi, Hungaria Indonesian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Romanian, Russian Swedish, Thai, Turkish Swedish, Thai, Turkish Swedish, Thai, Turkish         Service life of light source (economic mode)       1 lamp(s)         Lens system       Noise level *       33 dB         Multimedia
Native aspect ratio * 16:10 Interactive *   Number of colours 1.07 billion colours Noise level (economic mode) 29 dB  Keystone correction, vertical -30 - 30° On Screen Display (OSD)    Matrix size 1.65 cm (0.65") Arabic, Bulgarian, Simplified Chinese, Traditional Chinese, Tradition
Keystone correction, vertical  -30 - 30°  Matrix size  1.65 cm (0.65")  Light source  Light source type *  Service life of light source  Service life of light source  (economic mode)  Lamps quantity  Lamps (0SD)  On Screen Display (OSD)  On Screen Display (OSD)  On Screen Display (OSD)  Indicate the service life of light source to
Matrix size  Light source Light source type * Light source iffe of light source * Service life of light source (economic mode) Lamps quantity  Lens system  Zoom capability  1.65 cm (0.65")  Arabic, Bulgarian, Simplified Chinese, Croatian, Czech, Danish, Germ Dutch, English, Spanish, Finnisi French, Greek, Hindi, Hungaria Indonesian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Romanian, Russian Swedish, Thai, Turkish  33 dB  Multimedia
Light source Light source type * Lamp Service life of light source * 6000 h Service life of light source (conomic mode) Lamps quantity  Lens system Zoom capability  Chinese, Traditional Chinese, Croatian, Czech, Danish, Germ. Dutch, English, Spanish, Finnist French, Greek, Hindi, Hungaria Indonesian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Romanian, Russian Swedish, Thai, Turkish  Noise level * 33 dB  Multimedia
Service life of light source * Service life of light source * Service life of light source (economic mode) Lamps quantity  Lens system  Zoom capability  Con Screen Display (OSD) languages French, Greek, Hindi, Hungaria Indonesian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Romanian, Russian Swedish, Thai, Turkish  Noise level *  Multimedia
(economic mode)  Lamps quantity  1 lamp(s)  Portuguese, Romanian, Russian Swedish, Thai, Turkish  Noise level * 33 dB  Multimedia
Lens system Zoom capability  Noise level * 33 dB  Multimedia
Lens system  Zoom capability  Multimedia
Zoom capability X
Throw ratio 0.40·1 Built-in speaker(s) * ✓
Offset 105% RMS rated power 10 W
Video Number of built-in speakers 1
Full HD * Design
3D * Presentation
Supported 3D formats  Frame Sequential, Frame packing, Side by side, Top and bottom  Frame Sequential, Frame packing, Side by side, Top and bottom  Product type * Short throw projector White
Supported graphics resolutions  640 x 480 (VGA), 1920 x 1200 (WUXGA)  Cable lock slot  Cable lock slot type  Kensington
Supported video modes 480i, 480p, 576i, 576p, 720p, 1080i, 1080p <b>Power</b>
Ports & interfaces Power source * AC
S-Video inputs quantity 1  Power consumption (typical) * 260 W
USB 2.0 ports quantity * 1  AC input voltage 100 - 240 V
Mini-USB 2.0 ports quantity  AC input voltage  100 - 240 V

Ports & interfaces		Power	
Audio (L/R) in *	1	AC input frequency	50 / 60 Hz
Serial interface type * PC Audio in PC Audio out VGA (D-Sub) ports quantity * HDMI ports quantity * Composite video in *	RS-232 ✓ ✓ 3	Operational conditions	
		Operating temperature (T-T)	0 - 40 °C
		Weight & dimensions	
	2	Width	296 mm
	1	Depth	239 mm
DVI port *	×	Height	120 mm
AC (power) in	✓	Weight *	2.6 kg
Network		Packaging content	
Ethernet LAN *	✓	Remote control included *	✓
		Remote control type	IR
		Batteries included	✓
		Cables included	AC
		Manual	✓
		Logistics data	
		Quantity per pack	1 pc(s)
		Harmonized System (HS) code	85286200



4718755083808

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.