KYOCERA ECOSYS P4140dn 1200 x 1200 DPI A3

Brand : KYOCERA

Product name : ECOSYS P4140dn

Product code: 1102Y43NL0

- Double-sided print
- Toner save mode
- Beneficial for the environment with long-life components and low energy consumption
- Print using direct Wi-Fi

A3, 40/22 ppm, 1200 x 1200 DPI, ARM Cortex-A9 1200 MHz, USB 2.0, Ethernet, 220/240 VAC, 50/60 Hz, 477 x 410 x 343 mm, 21 kg

KYOCERA ECOSYS P4140dn 1200 x 1200 DPI A3:

This compact A3 black and white printer offers an expandable paper capacity of up to 6 paper trays for flexible paper handling. Plus this device knows exactly how to impress with comprehensive standard security features for optional SSD and ECOSYS long-life technology.
KYOCERA ECOSYS P4140dn. Print technology: Laser. Number of print cartridges: 1, Maximum duty cycle: 150000 pages per month. Maximum resolution: 1200 x 1200 DPI. Maximum ISO A-series paper size: A3. Print speed (black, normal quality, A4/US Letter): 40 ppm, Duplex printing. Display: LCD. Network ready. Product colour: Black, White

Printing

Duplex printing mode	Auto
Print resolution black	1200 x 1200 DPI
Colour *	✖
Print technology *	Laser
Duplex printing *	✓
Maximum resolution *	1200 x 1200 DPI
Print speed (black, normal quality, A4/US Letter) *	40 ppm
Print speed (black, normal quality, A3)	22 ppm
Duplex print speed (black, normal quality, A4/US Letter)	28 ppm
Warm-up time	18 s
Time to first page (black, normal)	6.3 s
Watermark printing	✓
Secure printing	✓

Features

Maximum duty cycle *	150000 pages per month
Recommended duty cycle	10000 - 15000 pages per month
Printing colours *	Black
Number of print cartridges *	1
Page description languages *	Epson LQ, IBM ProPrinter XL24E, JPEG, OpenXPS, PCL 5c, PCL 6, PDF 1.7, TIFF, XPS
Printer fonts	Barcode, Bitmap, PCL
Number of PCL fonts	93
Number of barcode fonts	79
Number of bitmap fonts	1
Number of Windows fonts	8
Linear (1D) barcodes supported	EAN 128, EAN-13, EAN-8, PDF417
Country of origin	Vietnam
Replacement cartridges	TK-7310 (15.000 pagina's)

Network

Near Field Communication (NFC)	✖
Bluetooth	✖
Mobile printing technologies	Apple AirPrint, Google Cloud Print, Kyocera Mobile Print, Mopria Print Service

Performance

Internal memory *	512 MB
Maximum internal memory	2500 MB
Built-in processor	✓
Processor family	ARM Cortex
Processor model	A9
Processor frequency	1200 MHz
Sound pressure level (printing)	50.7 dB
Sound pressure level (quiet mode)	47.9 dB

Design

Market positioning *	Business
Product colour *	Black, White
Built-in display *	✓
Display	LCD
Colour display	✖
Control type	Buttons
Certification	TÜV / GS, CE

Power

Power consumption (printing) *	632 W
Power consumption (max)	1415 W
Power consumption (ready)	15 W
Power consumption (standby)	11 W
Power consumption (off)	0.5 W
Energy Star Typical Electricity Consumption (TEC)	1.9 kWh/week
AC input voltage	220 - 240 V
AC input frequency	50/60 Hz

Input & output capacity

Total number of input trays *	1
Total input capacity *	500 sheets
Total output capacity *	500 sheets
Paper tray 1 input capacity	500 sheets
Multi-Purpose tray	✔
Multi-Purpose tray input capacity	100 sheets
Maximum number of input trays	5
Maximum input capacity	2600 sheets
Maximum output capacity	750 sheets

Paper handling

Maximum ISO A-series paper size *	A3
Maximum print size	297 x 432 mm
Paper tray media types *	Plain paper, Thick paper
ISO A-series sizes (A0...A9) *	A3, A4, A4+, A5, A6
ISO B-series sizes (B0...B9)	B4, B5
Non-ISO print media sizes	Legal, Letter
Envelopes sizes	C5, DL
Custom media width	70 - 148 mm
Custom media length	297 - 1220 mm
Paper tray media weight	60 - 120 g/m²
Multi-Purpose Tray media weight	60 - 220 g/m²

Ports & interfaces

Direct printing *	✔
USB port *	✔
USB 2.0 ports quantity	2
Optional connectivity	Ethernet, Parallel, Wireless LAN

Network

Network ready	✔
Wi-Fi *	✖
Ethernet LAN *	✔
Cabling technology	10/100/1000Base-T(X)
Ethernet LAN data rates	10,100,1000 Mbit/s

System requirements

Windows operating systems supported	✔
Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.9 Mavericks
Linux operating systems supported	✔

Operational conditions

Operating temperature (T-T)	10 - 32.5 °C
Storage temperature (T-T)	-20 - 40 °C
Operating relative humidity (H-H)	15 - 80%
Storage relative humidity (H-H)	10 - 90%
Operating altitude	0 - 3500 m
Non-operating altitude	0.6 - 15000 m

Sustainability

Sustainability certificates	Blue Angel, ENERGY STAR

Weight & dimensions

Width	477 mm
Depth	410 mm
Height	343 mm
Weight	21 kg

Packaging data

Package width	581 mm
Package depth	542 mm
Package height	460 mm
Package weight	26 kg

Packaging content

Cartridge(s) included	✔
Included cartridge capacity (black)	7500 pages
Power cord included	✔
USB cable included	✖

Logistics data

Harmonized System (HS) code	84433210

0632983061169

632983061169

0632983061176

632983061176