

Manhattan Charging Cabinet/Cart via USB-C x32 Devices, Trolley, Power Delivery 18W per port (576W total), Suitable for iPads/other tablets/phones/smaller chromebooks, Bays 330x22x235mm, Device charging cables not included, Lockable (PIN code), EU & UK power cords



Brand : Manhattan

Product code: 716000

Product name : Charging Cabinet/Cart via USB-C x32 Devices, Trolley, Power Delivery 18W per port (576W total), Suitable for iPads/other tablets/phones/smaller chromebooks, Bays 330x22x235mm, Device charging cables not included, Lockable (PIN code), EU & UK power cords

Charging Cabinet via USB-C x32 Devices, Trolley, Power Delivery 3A/18W per port (576W total), Suitable for iPads/other tablets/phones/smaller chromebooks, Bays 330x22x235mm, Device charging cables not included, Lockable (PIN Code), Euro 2-pin Plug
 Manhattan Charging Cabinet/Cart via USB-C x32 Devices, Trolley, Power Delivery 18W per port (576W total), Suitable for iPads/other tablets/phones/smaller chromebooks, Bays 330x22x235mm, Device charging cables not included, Lockable (PIN code), EU & UK power cords. Type: Portable device management cart, Product colour: Black, Cord length: 2 m. Supported portable devices: Smartphone, Tablet, Device connectors supported: USB, Charging source: USB Type-C. AC input voltage: 110 - 240 V, AC input frequency: 50/60 Hz, Output voltage: 5 - 12 V. Width: 375 mm, Depth: 560 mm, Height: 575 mm. Cables included: AC

Design		Power	
Type *	Portable device management cart	AC input frequency	50/60 Hz
Castor wheels	✓	Output voltage	5 - 12 V
Cord length	2 m	Input current	16 A
Product colour *	Black	Output current	3 A
Features		Operational conditions	
Number of devices supported *	32	Operating temperature (T-T)	0 - 40 °C
Supported portable devices *	Smartphone, Tablet	Operating relative humidity (H-H)	20 - 80%
Charging source	USB Type-C	Storage temperature (T-T)	-15 - 45 °C
Device connectors supported *	USB	Weight & dimensions	
Power protection features	Over current, Over voltage, Short circuit	Width	375 mm
LED indicators	Status	Depth	560 mm
Locking	✓	Height	575 mm
Lock type	Code	Weight	45 kg
Ventilation	✓	Housing thickness	1.5 mm
Certification	PD 3.0 CE RoHS	Packaging content	
Power		Cables included	AC
AC input voltage	110 - 240 V	Manual	✓



0766623716000



766623716000

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.