

## APC Smart-UPS Line-Interactive 9 AC outlet(s)

Brand : APC Product code: SMT3000RMI2U

Product name: Smart-UPS

Smart-UPS, 3000VA, RM 2U, LCD, 230V

APC Smart-UPS. UPS topology: Line-Interactive, Waveform: Sine, Input operation voltage (min): 151 V. AC outlet types: C13 coupler, C19 coupler, Power plug: C20 coupler, AC outlets quantity: 9 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery capacity: 547 VAh, Typical backup time at full load: 3.2 min. Form factor: Rackmount, Product colour: Black, Rack capacity: 2U. Width: 480 mm, Depth: 683 mm, Height: 86 mm





Features		Design	
UPS topology * Waveform * Input operation voltage (min) * Input operation voltage (max) * Input frequency * Output operation voltage (min) Output operation voltage (max) Automatic Voltage Regulation (AVR, Surge energy rating Hold time (min) Hold time (max) Efficiency Noise level Audible alarm(s) Auto-restart	Line-Interactive Sine 151 V 302 V 50/60 Hz 220 V 240 V  4 ms 8 ms 99% 55 dB	Form factor * Rack capacity Cable length Product colour * LED indicators  Certification  Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude	Rackmount 2U 2 m Black Status CE, EAC, EN 60950, EN/IEC 62040-1, EN/IEC 62040-2, GS Mark, IRAM, RCM, VDE, WEEE, REACH, PEP, EOLI  0 - 40 °C -15 - 45 °C 0 - 95% 0 - 95% 0 - 3000 m 0 - 15000 m
Ports & interfaces	<b>v</b>	Technical details	0 - 13000 III
AC outlet types Conservation Co	C13 coupler, C19 coupler C20 coupler 9 AC outlet(s) 3	Sustainability certificates RoHS, ENERGY STAR  Weight & dimensions  Width 480 mm  Depth 683 mm  Height 86 mm  Weight 44.3 kg  Package width 600 mm  Package depth 980 mm  Package height 254 mm  Package weight 51.7 kg	
USB port			86 mm
Battery technology Battery capacity Typical backup time at full load Typical backup time at half load Battery life (max) Battery recharge time Hot-swap battery Automatic battery test Cold start	Sealed Lead Acid (VRLA) 547 VAh 3.2 min 11.5 min 5 year(s) 3 h  ✓		600 mm 980 mm 254 mm
		Packaging data	
		Rack mount kit Cables included Quick installation guide Software CD	RS-232, USB cable
		Logistics data	
		Products per pallet	8 pc(s)
		Other features	
		Nominal output voltage Nominal input voltage	230 V 230 V





731304284642

0731304284642

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.