Viewsonic TD3207 computer monitor 81.3 cm (32") 1920 x 1080 pixels Full HD LED Touchscreen

Brand : Viewsonic Product code: TD3207

Product name: TD3207

- SuperClear ® AMVA technology
- Long-lasting usage
- Supreme reliability and durability

32", VA, FHD, 1920 x 1080, 3000:1, LED, 450mits, 8bit, 5ms

Viewsonic TD3207. Display diagonal: 81.3 cm (32"), Display resolution: $1920 \times 1080 \text{ pixels}$, HD type: Full HD, Display technology: LED, Response time: 5 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178° , Viewing angle, vertical: 178° . Built-in speaker(s). VESA mounting







Display diagonal * 81.3 cm (32") Display resolution * 1920 x 1080 pixels Number of upstream port type Full HD HDMI * Native aspect ratio * 16:9 Display resolution * 16:9 HDMI ports quantity LED HDMI ports quantity 1 Display Persolutity 1 Display tersion 1.4 Panel type * VA DisplayPorts quantity 1 Backlight type LED Audio output 1 Touchscreen * V RS-232 ports 1 Touchscreen technology Multi-touch VESA mounting * VESA mounting				
Display resolution 1920 x 1080 pixels Number of upstream ports 1	Display		Ports & interfaces	
HD type * Full HD HDMI * √ ADMI *	Display diagonal *	81.3 cm (32")	USB upstream port type USB Type-B	
Native aspect ratio * 16:9 HDMI ports quantity 1 Display technology * LED HDMI version 1.4 Panel type * VA DisplayPorts quantity 1 Backlight type LED Audio output 1 Touchscreen * VA RS-232 ports 1 Touchscreen technology Capacitive Frounding * VESA mounting * VESA mounti	Display resolution *	1920 x 1080 pixels	Number of upstream ports 1	
Display technology * LED HDMI version 1.4 Panel type * VA DisplayPorts quantity 1 Backlight type LED Addio output 1 Touchscreen * ✓ RS-232 ports 1 Touchscreen technology Capacitive Frommics Touch technology Multi-touch VESA mounting * ✓ VESA mounting * VESA mounting * VESA mounting * VESA mounting	HD type *	Full HD	HDMI* ✓	
Panel type * VA DisplayPorts quantity 1 Backlight type LED Audio output 1 Touchscreen * V RS-232 ports 1 Touchscreen technology Capacitive Ergonomics Touch technology Multi-touch VESA mounting * V Number of simultaneous touchpoints Response time 5 ms Energy efficiency class (SDR) * E Response time 5 ms Energy efficiency class (SDR) * E Response time 5 ms Energy efficiency class (SDR) per 1000 25.8 kWh hours * V Contrast ratio (typical) * 3000:1 hours * 43 W Maximum refresh rate * 60 Hz Power consumption (typical) * 43 W Viewing angle, horizontal 178° Power consumption (max) 45.5 W Viewing angle, vertical 178° AC input voltage 100 - 240 V Display number of colours * 16.78 million colours AC input frequency 50/60 Hz Pixel pitch 0.364 x 0.364 mm Power supply type AC Horizontal scan range 15 - 73 kHz Digital horizontal frequency 15 - 73 kHz Oligital horizontal frequency 15 - 73 kHz Oligital vertical frequency 47 - 75 Hz Digital vertical frequency 47 - 75 Hz Oligital vertical frequen	Native aspect ratio *	16:9	HDMI ports quantity 1	
Backlight type LED Audio output 1 Touchscreen *	Display technology *	LED	HDMI version 1.4	
Touchscreen *	Panel type *	VA	DisplayPorts quantity 1	
Touch screen technology Touch technology Multi-touch Number of simultaneous touch points Response time Screen shape * Flat Contrast ratio (typical) * South (different or simultaneous) Touch technology Response time Some Serven shape * Flat Contrast ratio (typical) * South (different or simultaneous) Touch technology Response time Some Simultaneous South (different or simultaneous) Touch technology Response time Some Simultaneous Some Some Simultaneous Some Some Some Some Some Some Some Some	Backlight type	LED	Audio output 1	
Touch technology Number of simultaneous touchpoints Response time Soreen shape * Flat Contrast ratio (typical) * 3000:1 Contrast ratio (typ	Touchscreen *	✓	RS-232 ports 1	
Touch technology Number of simultaneous touchpoints Response time Soreen shape * Flat Contrast ratio (typical) * 3000:1 Contrast ratio (typical) * 3000:1 Contrast ratio (dynamic) Maximum refresh rate * 60 Hz Viewing angle, horizontal Display number of colours * Horizontal scan range Digital horizontal frequency Digital horizontal frequency Digital vertical frequency Surface hardness TH Weight & dimensions RGB colour space NTSC Width (with stand) Display brightness 450 cd/m² Height (with stand) Depth (without stand) Depth (witho	Touchscreen technology	Capacitive	Ergonomics	
touchpoints Response time Screen shape * Flat Energy consumption (SDR) per 1000 Contrast ratio (typical) * 3000:1 Power consumption (typical) * 43 W Maximum refresh rate * 60 Hz Power consumption (standby) * 0.5 W Viewing angle, horizontal 178° Power consumption (max) 45.5 W Viewing angle, vertical 178° AC input voltage 100 - 240 V Display number of colours * 16.78 million colours AC input frequency 50/60 Hz Pixel pitch 0.364 x 0.364 mm Power supply type AC Horizontal scan range 15 - 73 kHz Operational conditions Vertical scan range 47 - 75 Hz Digital horizontal frequency 15 - 73 kHz Operating temperature (T-T) 0 - 40 °C Operating temperature (T-T) 0 - 90% Weight & dimensions Weight & dimensions Weight & dimensions Weight & dimensions Weight & dimensions NTSC Width (with stand) 747 mm Colour gamut 72% Depth (with stand) 451 mm Display brightness 450 cd/m² Height (with stand) 74.7 cm Depth (without stand) 74.7 cm Depth (without stand) 45.1 cm NVIDIA G-SYNC * AMD FreeSync *	Touch technology	Multi-touch	-	
Screen shape * Flat Energy enroller(cy class (SDR) Screen shape * Flat Energy consumption (SDR) per 1000 hours * 3000:1 hours * 43 W Maximum refresh rate * 60 Hz Power consumption (typical) * 43 W Viewing angle, horizontal 178° Power consumption (max) 45.5 W Viewing angle, vertical 178° AC input voltage 100 - 240 V Display number of colours * 16.78 million colours AC input frequency 50/60 Hz Pixel pitch 0.364 x 0.364 mm Power supply type AC Horizontal scan range 15 - 73 kHz Operational conditions Vertical scan range 47 - 75 Hz Digital horizontal frequency 15 - 73 kHz Operating temperature (T-T) 0 - 40 °C Operating relative humidity (H-H) 20 - 90% Weight & dimensions Weight & dimensions Weight & dimensions Weight & dimensions Height (with stand) 451 mm Display brightness 450 cd/m² Height (with stand) 12.8 kg Performance NYIDIA G-SYNC * AMD FreeSync * Height (without stand) 45.1 cm Height (without stand) 6.4 cm	Number of simultaneous touchpoints	10	Power	
Screen shape * Flat Energy consumption (SDR) per 1000 25.8 kWh Contrast ratio (typical) * 3000:1 hours * 43 W Maximum refresh rate * 60 Hz Power consumption (typical) * 43 W Maximum refresh rate * 60 Hz Power consumption (standby) * 0.5 W Viewing angle, horizontal 178° Power consumption (max) 45.5 W Viewing angle, vertical 178° AC input voltage 100 - 240 V Display number of colours * 16.78 million colours AC input frequency 50/60 Hz Pixel pitch 0.364 x 0.364 mm Power supply type AC Horizontal scan range 15 - 73 kHz Operational conditions Vertical scan range 47 - 75 Hz Digital horizontal frequency 15 - 73 kHz Operating temperature (T-T) 0 - 40 °C Operating relative humidity (H-H) 20 - 90% Weight & dimensions Weight & dimensions RGB colour space NTSC Width (with stand) 747 mm Colour gamut 72% Depth (with stand) 451 mm Display brightness 450 cd/m² Height (with stand) 12.8 kg Performance NVIDIA G-SYNC * Width (without stand) 74.7 cm Depth (without stand) 45.1 cm Height (without stand) 45.1 cm Height (without stand) 45.1 cm	Response time	5 ms	Energy efficiency class (SDR) * F	
Contrast ratio (typical) * 3000:1 hours * 25.8 kWn Contrast ratio (dynamic) 50000000:1 Power consumption (typical) * 43 W Maximum refresh rate * 60 Hz Power consumption (standby) * 0.5 W Viewing angle, horizontal 178° Power consumption (max) 45.5 W Viewing angle, vertical 178° AC input voltage 100 - 240 V Display number of colours * 16.78 million colours AC input frequency 50/60 Hz Pixel pitch 0.364 x 0.364 mm Power supply type AC Horizontal scan range 15 - 73 kHz Vertical scan range 47 - 75 Hz Digital horizontal frequency 15 - 73 kHz Operating temperature (T-T) 0 - 40 °C Operating relative humidity (H-H) 20 - 90% Weight & dimensions Weight & dimensions Weight & dimensions Weight & dimensions LED backlight Vertical frequency 47 - 75 M2 Weight (with stand) 747 mm Depth (with stand) 64 mm LED backlight Vertormance Width (with stand) 74.7 cm Depth (without stand) 74.7 cm Depth (without stand) 74.7 cm Depth (without stand) 45.1 cm Height (without stand) 6.4 cm	Screen shape *	Flat	Fraggy consumption (CDD) nor 1000	
Maximum refresh rate * 60 Hz Power consumption (standby) * 0.5 W Viewing angle, horizontal 178° Power consumption (max) 45.5 W Viewing angle, vertical 178° AC input voltage 100 - 240 V Display number of colours * 16.78 million colours AC input frequency 50/60 Hz Pixel pitch 0.364 x 0.364 mm Power supply type AC Horizontal scan range 15 - 73 kHz Vertical scan range 47 - 75 Hz Digital horizontal frequency 15 - 73 kHz Operational conditions Operating temperature (T-T) 0 - 40 °C Operating relative humidity (H-H) 20 - 90% Weight & dimensions Weight & dimensions RGB colour space NTSC Width (with stand) 747 mm Display brightness 450 cd/m² Height (with stand) 64 mm LED backlight ✓ Weight (with stand) 12.8 kg Performance NVIDIA G-SYNC * AMD FreeSync * Width (without stand) 45.1 cm Height (without stand) 6.4 cm	Contrast ratio (typical) *	3000:1	25 1 1 1 1 25 8 KWD	
Viewing angle, horizontal 178° Power consumption (max) 45.5 W Viewing angle, vertical 178° AC input voltage 100 - 240 V Display number of colours * 16.78 million colours AC input frequency 50/60 Hz Pixel pitch 0.364 x 0.364 mm Power supply type AC Horizontal scan range 15 - 73 kHz Vertical scan range 47 - 75 Hz Digital horizontal frequency 15 - 73 kHz Operating temperature (T-T) 0 - 40 °C Operating relative humidity (H-H) 20 - 90% Weight & dimensions Weight & dimensions Weight & dimensions Weight (with stand) 747 mm Colour gamut 72% Depth (with stand) 451 mm Display brightness 450 cd/m² Height (with stand) 12.8 kg Performance NVIDIA G-SYNC * AMD FreeSync * Width (without stand) 45.1 cm Height (without stand) 45.1 cm Height (without stand) 45.1 cm Height (without stand) 45.1 cm	Contrast ratio (dynamic)	50000000:1	Power consumption (typical) * 43 W	
Viewing angle, vertical Display number of colours * 16.78 million colours AC input voltage 50/60 Hz AC input frequency 50/60 Hz Power supply type AC Digital prizontal frequency Digital vertical frequency Fixed particles are narge AT - 75 Hz Digital vertical frequency TH Weight & dimensions Weight (with stand) Display brightness 450 cd/m² Height (without stand) Performance NVIDIA G-SYNC * AMD FreeSync * AC input voltage AC input frequency 50/60 Hz AC input frequency 50/60 Hz AC input frequency 50/60 Hz AC input voltage AC input frequency 50/60 Hz AC input voltage AC input frequency 50/60 Hz AC input frequency 50/60 Hz AC Depational conditions Operating temperature (T-T) 0 - 40 °C Operating relative humidity (H-H) 20 - 90% Weight & dimensions Width (with stand) 747 mm 451 mm Depth (with without stand) 74.7 cm Depth (without stand) 45.1 cm Height (without stand) 6.4 cm	Maximum refresh rate *	60 Hz	Power consumption (standby) * 0.5 W	
Display number of colours * 16.78 million colours AC input frequency 50/60 Hz Pixel pitch 0.364 x 0.364 mm Power supply type AC Horizontal scan range 15 - 73 kHz Vertical scan range 47 - 75 Hz Digital horizontal frequency 15 - 73 kHz Digital vertical frequency 47 - 75 Hz Surface hardness 7H RGB colour space NTSC Width (with stand) 747 mm Display brightness 450 cd/m² Height (with stand) 451 mm Display brightness 450 cd/m² Height (with stand) 74.7 cm Performance NVIDIA G-SYNC * AMD FreeSync * AC input frequency 50/60 Hz	Viewing angle, horizontal	178°	Power consumption (max) 45.5 W	
Pixel pitch 0.364 x 0.364 mm Power supply type AC Horizontal scan range 15 - 73 kHz Vertical scan range 47 - 75 Hz Digital horizontal frequency 15 - 73 kHz Digital vertical frequency 47 - 75 Hz Surface hardness 7H RGB colour space NTSC Width (with stand) 747 mm Display brightness 450 cd/m² Height (with stand) 64 mm LED backlight ✓ Weight (with stand) 12.8 kg Performance NVIDIA G-SYNC * AMD FreeSync * Weight (without stand) 45.1 cm Height (without stand) 6.4 cm	Viewing angle, vertical	178°	AC input voltage 100 - 240 V	
Horizontal scan range Vertical scan range 47 - 75 Hz Digital horizontal frequency Digital vertical frequency Digital vertical frequency FreeSync* Digital horizontal frequency 15 - 73 kHz Digital horizontal frequency 15 - 73 kHz Digital vertical frequency 47 - 75 Hz Departing temperature (T-T) O - 40 °C Operating relative humidity (H-H) 20 - 90% Weight & dimensions Weight & dimensions Width (with stand) 747 mm 747 mm Depth (with stand) 451 mm Height (with stand) 12.8 kg Width (without stand) 74.7 cm Depth (without stand) 74.7 cm Depth (without stand) FreeSync* MUDIA G-SYNC* AMD FreeSync*	Display number of colours *	16.78 million colours	AC input frequency 50/60 Hz	
Vertical scan range 47 - 75 Hz Digital horizontal frequency 15 - 73 kHz Digital vertical frequency 47 - 75 Hz Operating temperature (T-T) Operating relative humidity (H-H) Operating r	Pixel pitch	0.364 x 0.364 mm	Power supply type AC	
Digital horizontal frequency Digital vertical frequency Digital vertical frequency A7 - 75 Hz Weight & dimensions Width (with stand) A51 mm Depth (with stand) A52 mm Depth (with stand) Depth (with stand) A53 mm Depth (with stand) A54 mm Weight (with stand) A55 mm Depth (with stand) A56 mm Weight (with stand) A57 mm Depth (with stand) A58 mm Weight (with stand) A59 mm Depth (with stand) A50 cd/m² A60 preeSync * Weight (without stand) A50 cd/m² A61 mm Weight (without stand) A62 mm Height (without stand) A63 cm Depth (without stand) A64 cm	Horizontal scan range		Operational conditions	
Digital vertical frequency 47 - 75 Hz Weight & dimensions Weight & dimensions Width (with stand) 747 mm Colour gamut 72% Depth (with stand) Display brightness 450 cd/m² Height (with stand) Weight & dimensions 747 mm 451 mm Height (with stand) 452 mm Weight (with stand) 454 mm Weight (with stand) 454 mm Weight (with stand) 747 cm Depth (without stand) 747 cm Depth (without stand) 748 mm Performance NVIDIA G-SYNC * AMD FreeSync * Width (without stand) Height (without stand) 64 cm	•		Operating temperature (T-T) 0 - 40 °C	
Surface hardness RGB colour space NTSC Width (with stand) Depth (with stand) 451 mm Display brightness 450 cd/m² Height (with stand) Weight (with stand) Weight (with stand) 451 mm 64 mm Weight (with stand) 12.8 kg Performance NVIDIA G-SYNC * AMD FreeSync * Weight (without stand) Performance Height (without stand) AMD FreeSync * Weight (without stand) 45.1 cm Height (without stand) 6.4 cm	. ,		Operating relative humidity (H-H) 20 - 90%	
RGB colour space NTSC Width (with stand) 747 mm Colour gamut 72% Depth (with stand) 451 mm Display brightness 450 cd/m² Height (with stand) 64 mm LED backlight ✓ Weight (with stand) 12.8 kg Performance Width (without stand) 74.7 cm Depth (without stand) 45.1 cm Height (without stand) 6.4 cm	Surface hardness		Weight & dimensions	
Colour gamut 72% Depth (with stand) 451 mm Display brightness 450 cd/m² Height (with stand) 64 mm LED backlight ✓ Weight (with stand) 12.8 kg Performance NVIDIA G-SYNC * AMD FreeSync * Pethodology Sync * NVIDIA G-SYNC * Height (without stand) 45.1 cm Height (without stand) 6.4 cm	RGB colour space	NTSC	Width (with stand) 747 mm	
Display brightness 450 cd/m² Height (with stand) 64 mm LED backlight ✓ Weight (with stand) 12.8 kg Performance NVIDIA G-SYNC * AMD FreeSync * Height (without stand) 74.7 cm Depth (without stand) 45.1 cm Height (without stand) 6.4 cm	Colour gamut		,	
LED backlight ✓ Weight (with stand) 12.8 kg Performance Width (without stand) 74.7 cm NVIDIA G-SYNC * X AMD FreeSync * X Height (without stand) 6.4 cm	Display brightness		• •	
Performance NVIDIA G-SYNC * AMD FreeSync * Width (without stand) Depth (without stand) 45.1 cm Height (without stand) 6.4 cm	LED backlight	•		
Depth (without stand) 45.1 cm AMD FreeSync * Height (without stand) 6.4 cm				
AMD FreeSync * Height (without stand) 6.4 cm			Depth (without stand) 45.1 cm	
AMD FreeSync * X Weight (without stand) 12.8 kg			Height (without stand) 6.4 cm	
	AMD FreeSync *	×	Weight (without stand) 12.8 kg	

Multimedia		Packaging data	
Built-in speaker(s) *	✓	Package width	863 mm
Number of speakers	2	Package depth	577 mm
Design		Package height	163 mm
International Protection (IP) code	IP54	Package weight	15.5 kg
Glass thickness	3 mm	Logistics data	
Certification	Regulations: CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, UKCA	Harmonized System (HS) code	85285210





766907010466

0766907010466

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.