Viewsonic PS501X data projector Short throw projector 3600 ANSI lumens DMD XGA (1024x768) White

Brand : Viewsonic　　　　　　　　　　**Product code:** PS501X

Product name : PS501X

PS501X, XGA, DLP, 3400 lumens, 1024 x 768, 30 - 300", 32dB, 2W, 3D, 292 x 115 x 236 mm, White Viewsonic PS501X. Projector brightness: 3600 ANSI lumens, Projection technology: DMD, Projector native resolution: XGA (1024x768). Light source type: Lamp, Service life of light source: 5000 h, Service life of light source (economic mode): 15000 h. Focus: Manual, Fixed focal length: 6.9 mm, Aperture range (F-F): 2.6 - 2.6. Analog signal format system: NTSC, PAL, SECAM, Supported graphics resolutions: 640 x 480 (VGA), 1920 x 1080 (HD 1080), Supported video modes: 480i, 480p, 576i, 576p, 720p, 1080i, 1080p. Serial interface type: RS-232, HDMI connector type: Full-size

Projector

Screen size compatibility *	1524 - 7620 mm (60 - 300")
Projection distance	0.74 - 3.72 m
Projector brightness *	3600 ANSI lumens
Projection technology *	DMD
Projector native resolution *	XGA (1024x768)
Contrast ratio (typical) *	22000:1
Number of colours	1.07 billion colours
Horizontal scan range	15 - 102 kHz
Vertical scan range	23 - 120 Hz
Keystone correction, vertical	-37 - 30°
Matrix size	1.4 cm (0.55")

Light source

Light source type *	Lamp
Service life of light source *	5000 h
Service life of light source (economic mode)	15000 h
Lamp power	190 W
Lamps quantity	1 lamp(s)

Lens system

Focus *	Manual
Fixed focal length	6.9 mm
Aperture range (F-F)	2.6 - 2.6
Zoom capability	✓
Zoom ratio	2.0:1
Throw ratio	0.61
Offset	130%

Video

Analog signal format system *	NTSC, PAL, SECAM
Supported graphics resolutions	640 x 480 (VGA), 1920 x 1080 (HD 1080)
Supported video modes	480i, 480p, 576i, 576p, 720p, 1080i, 1080p

Network

Smart TV *	✗
Ethernet LAN *	✗
Wi-Fi *	✗

Storage

Card reader integrated *	✗

Features

Interactive *	✗
Noise level (economic mode)	27 dB
HDCP	✓
On Screen Display (OSD)	✓
On Screen Display (OSD) languages	Arabic, Simplified Chinese, Traditional Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, Greek, Indonesian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Thai, Turkish, Vietnamese
Number of OSD languages	23
Noise level *	31 dB

Multimedia

Built-in speaker(s) *	✓
RMS rated power	2 W

Design

Market positioning *	Presentation
Product type *	Short throw projector
Product colour *	White
Placement	Desktop, Ceiling

Display

Built-in display *	✗

Power

Power source *	AC

Ports & interfaces

HDMI connector type	Full-size
HDMI version	1.4
USB 2.0 ports quantity *	1
Mini-USB 2.0 ports quantity	1
Serial interface type *	RS-232
PC Audio in	✔
PC Audio out	✔
VGA (D-Sub) ports quantity *	3
HDMI ports quantity *	1
Composite video in *	1
DVI port *	✘
Mobile High-Definition Link (MHL)	✘
AC (power) in	✔

Power

Power consumption (typical) *	260 W
Power consumption (standby) *	0.5 W
AC input voltage	100-240 V
AC input frequency	50/60 Hz

Operational conditions

Operating temperature (T-T)	0 - 40 °C

Weight & dimensions

Width	292 mm
Depth	236 mm
Height	115 mm
Weight *	2.6 kg
Package width	365 mm
Package depth	300 mm
Package height	188 mm
Package weight	3.62 kg

Packaging content

Remote control included *	✔
Cables included	AC, VGA
Manual	✔

Logistics data

Harmonized System (HS) code	85286200

0766907958119

766907958119