



## HP E24d G4 60.5 cm (23.8") 1920 x 1080 pixels Full HD Black

Brand : HP

Product code: 6PA50A4

Product name : E24d G4

E24d G4 FHD USB-C Docking Monitor

HP E24d G4 60.5 cm (23.8") 1920 x 1080 pixels Full HD Black:

Create the perfect productivity hub

Inspire joy on your desk with the clean connectivity of the HP E24d G4 FHD USB-C Docking Monitor. Add your everyday accessories at the display, then add your PC with just one USB-C<sup>[1]</sup> cable. Empower IT to remotely manage HP devices from anywhere on the network through RJ-45.<sup>[2,3]</sup>

HP E24d G4. Display diagonal: 60.5 cm (23.8"), Display resolution: 1920 x 1080 pixels, HD type: Full HD, Response time: 5 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in USB hub, USB hub version: 3.2 Gen 1 (3.1 Gen 1). VESA mounting, Height adjustment. Product colour: Black




Display		Ports & interfaces	
Display diagonal *	60.5 cm (23.8")	DisplayPort version	1.2
Display resolution *	1920 x 1080 pixels	Headphone out *	✓
HD type *	Full HD	<b>Ergonomics</b>	
Native aspect ratio *	16:9	VESA mounting *	✓
Panel type *	IPS	Panel mounting interface	100 x 100 mm
Touchscreen *	✗	Cable lock slot *	✗
Display brightness (typical)	250 cd/m <sup>2</sup>	Height adjustment *	✓
Response time	5 ms	Height adjustment	15 cm
Screen shape *	Flat	Pivot	✓
Supported graphics resolutions	640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA), 1024 x 768 (XGA), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1280 x 768 (WXGA), 1280 x 800 (WXGA), 1440 x 900, 1600 x 900, 1680 x 1050 (WSXGA+), 1920 x 1080 (HD 1080)	Tilt angle range	-5 - 20°
		On Screen Display (OSD)	✓
		Plug and Play	✓
		<b>Power</b>	
		Energy efficiency class (SDR) *	D
Contrast ratio (typical) *	1000:1	Energy consumption (SDR) per 1000 hours *	18 kWh
Contrast ratio (dynamic)	5000000:1	Power consumption (typical) *	70 W
Viewing angle, horizontal	178°	Power consumption (standby) *	0.5 W
Viewing angle, vertical	178°	Power consumption (max)	175 W
Pixel pitch	0.274 x 0.274 mm	AC input voltage	100 - 240 V
Digital horizontal frequency	30 - 80 kHz	<b>Operational conditions</b>	
Digital vertical frequency	50 - 60 Hz	Operating temperature (T-T)	5 - 35 °C
RGB colour space	NTSC	Operating relative humidity (H-H)	20 - 80%
Colour gamut	72%	<b>Packaging content</b>	
<b>Performance</b>		Cables included	DisplayPort, HDMI, USB Type-C
HP segment	Business	<b>Weight &amp; dimensions</b>	
<b>Multimedia</b>		Width (with stand)	539.4 mm
Built-in camera *	✓	Depth (with stand)	206.8 mm
Built-in microphone	✓	Height (with stand)	486.4 mm
<b>Design</b>		Weight (with stand)	6.86 kg
Market positioning *	Business	Width (without stand)	53.9 cm
Product colour *	Black	Depth (without stand)	4.85 cm
Country of origin	China		

Ports & interfaces		Weight & dimensions	
Built-in USB hub *	✓	Height (without stand)	32.3 cm
USB hub version	3.2 Gen 1 (3.1 Gen 1)	<b>Packaging data</b>	
USB upstream port type	USB Type-C	Package width	539.4 mm
Number of upstream ports	1	Package depth	206.8 mm
Number of USB Type-C upstream ports quantity	1	Package height	486.4 mm
USB Type-A downstream ports quantity	4	Package weight	11 kg
USB Type-C downstream ports quantity	1	<b>Sustainability</b>	
USB Type-C DisplayPort Alternate Mode	✓	Sustainable technologies and materials	Arsenic-free display glass; Low halogen; Mercury-free display backlights
USB Power Delivery	✓	<b>Logistics data</b>	
USB Power Delivery up to	100 W	Harmonized System (HS) code	85285210
HDMI *	✓	<b>Other features</b>	
HDMI ports quantity	1	Height	323.3 mm
HDMI version	1.4	Width	539.4 mm
DisplayPorts quantity	1	Depth	48.5 mm



0195697978883



195697978883




0195697978838



195697978838



0195697978845



195697978845



0195697978852



195697978852



0195697978869



195697978869




0195697978876



195697978876



0195697978906



195697978906




0195697978913



195697978913



0195697978920



195697978920



0195697978937



195697978937



0195697978944



195697978944



0195697978951



195697978951



0195697978968



195697978968



0195697978975



195697978975



0195697978982



195697978982



0195697978999



195697978999



0195697979002



195697979002



0195697978821



195697978821



4573595618128

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 19-MAY-2023. Prints or copies of Information are only valid on the printed Publication date