

Linksys LGS328C-EU network switch Managed Gigabit Ethernet (10/100/1000) Black

Brand : Linksys

Product code: LGS328C-EU

Product name : LGS328C-EU



- 10G SFP+ Uplink Ports (4)

- Advanced Network Security and QoS

24-Port Managed Gigabit Ethernet Switch with 4 10G SFP+ Uplinks

Linksys LGS328C-EU. Switch type: Managed. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet

(10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 24. MAC address table: 16000 entries,

Switching capacity: 128 Gbit/s. Networking standards: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1s, IEEE

802.1w, IEEE 802.3ad. Rack mounting

Management features		Protocols	
Switch type *	Managed	IPv4 FIB entries	63
Quality of Service (QoS) support	✓	IPv6 FIB entries	21
Ports & interfaces		Design	
Basic switching RJ-45 Ethernet ports quantity *	24	Rack mounting *	✓
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Stackable *	✓
Network		Product colour	Black
Networking standards *	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1s, IEEE 802.1w, IEEE 802.3ad	LED indicators	Fault, Power
10G support *	✓	Country of origin	Taiwan
Port mirroring	✓	Performance	
IP routing	✓	Internal memory	512 MB
Link aggregation	✓	Firmware upgradeable	✓
Broadcast storm control	✓	Power	
Rate limiting	✓	Power source *	AC
Spanning tree protocol	✓	Power supply included *	✓
Head-of-line (HOL) blocking	✓	AC input voltage	100 - 240 V
VLAN support	✓	AC input frequency	50 - 60 Hz
Virtual LAN features	Port-based VLAN	Input current	0.7 A
Number of VLANs	256	Power consumption (typical)	23.95 W
Data transmission		Power over Ethernet (PoE)	
Switching capacity *	128 Gbit/s	Power over Ethernet (PoE) *	✗
Forwarding rate	95.23 Mpps	Operational conditions	
MAC address table *	16000 entries	Operating temperature (T-T)	0 - 45 °C
Jumbo frames support	✓	Storage temperature (T-T)	-20 - 70 °C
Jumbo frames	12000	Operating relative humidity (H-H)	10 - 90%
Security		Storage relative humidity (H-H)	5 - 95%
DHCP features	DHCP snooping	Weight & dimensions	
Access Control List (ACL)	✓	Width	330 mm
IGMP snooping	✓	Depth	230 mm
IP-MAC-Port binding	✓	Height	44 mm
Authentication	Guest VLAN	Weight	1.99 kg
Authentication type	RADIUS	Packaging data	
Protocols		Package type	Box
Management protocols	HTTP, HTTPS	Logistics data	
		Harmonized System (HS) code	85176990



0745883810161



745883810161



4260184670659



0745883814589



745883814589

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.