FAT•N

Eaton Ellipse ECO 1600 USB IEC Standby (Offline) 1.6 kVA 1000 W 8 AC outlet(s)

Brand : Eaton Product code: EL1600USBIEC

Product name: Ellipse ECO 1600 USB IEC

Ellipse ECO 1600 USB IEC

Eaton Ellipse ECO 1600 USB IEC Standby (Offline) 1.6 kVA 1000 W 8 AC outlet(s):

The Eaton Ellipse ECO is a slim-line power protection with built-in high performance surge-protection device (compliant with IEC 61643-1 standard). With an efficient electrical design and the EcoControl function (USB models) the Eaton Ellipse ECO helps you make energy savings of up to 25 per cent compared to previous-generation UPSs.

Eaton Ellipse ECO 1600 USB IEC. UPS topology: Standby (Offline), Output power capacity: 1.6 kVA, Output power: 1000 W. AC outlet types: C13 coupler, Power plug: C14 coupler, AC outlets quantity: 8 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Typical backup time at half load: 11 min. Form factor: Tower, Product colour: Black, Rack capacity: 2U. Width: 81 mm, Depth: 312 mm, Height: 305 mm



Features		Battery	
UPS topology * Output power capacity * Output power * Input operation voltage (min) * Input operation voltage (max) * Input frequency * Output operation voltage (min) Output operation voltage (max) Emergency Power Off (EPO) Surge protection Surge protection features Audible alarm(s) Audible alarm modes	Standby (Offline) 1.6 kVA 1000 W 161 V 284 V 50/60 Hz 220 V 240 V Fax, Modem, Network, Telephone Battery replacement	Typical backup time at half load Hot-swap battery Automatic battery test Cold start	11 min
		Posign Form factor * Rack capacity Product colour * LED indicators Safety Technical details	Tower 2U Black Battery replacement IEC 62040-1, IEC 60950-1, IEC 62040-2, CB Report, CE mark, IEC 61643-1
Ports & interfaces		Harmonized System (HS) code	85078000
AC outlet types Power plug AC outlets quantity USB 2.0 ports quantity Modem (RJ-11) ports Ethernet LAN (RJ-45) ports	C13 coupler C14 coupler 8 AC outlet(s) 1 1	Weight & dimensions Width Depth Height Weight	81 mm 312 mm 305 mm 7.8 kg
Battery		Packaging data	
Battery technology	Sealed Lead Acid (VRLA)	Bundled software Other features	Eaton Intelligent Power
		Input connection type Mac compatibility Nominal output voltage Nominal input voltage Compatible operating systems Overload protection	IEC 220-240 V 230 V Windows 7/Vista/XP\r Mac OS X\r Linux



3553340621635

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.