



Eaton Ellipse ECO 800 USB IEC Standby (Offline) 0.8 kVA 500 W 4 AC outlet(s)

Brand : Eaton

Product code: EL800USBIEC

Product name : Ellipse ECO 800 USB IEC

Ellipse ECO 800 USB IEC

Eaton Ellipse ECO 800 USB IEC Standby (Offline) 0.8 kVA 500 W 4 AC outlet(s):

The Eaton Ellipse ECO is a slim-line power protection with built-in high performance surge-protection device (compliant with IEC 61643-1 standard). With an efficient electrical design and the EcoControl function (USB models) the Eaton Ellipse ECO helps you make energy savings of up to 25 per cent compared to previous-generation UPSs.

Eaton Ellipse ECO 800 USB IEC. UPS topology: Standby (Offline), Output power capacity: 0.8 kVA, Output power: 500 W. AC outlet types: C13 coupler, Power plug: C14 coupler, AC outlets quantity: 4 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Typical backup time at half load: 11 min. Form factor: Tower, Product colour: Black, Rack capacity: 2U. Width: 81 mm, Depth: 235 mm, Height: 263 mm



Features		Battery	
UPS topology *	Standby (Offline)	Typical backup time at half load	11 min
Output power capacity *	0.8 kVA	Hot-swap battery	✗
Output power *	500 W	Automatic battery test	✓
Input operation voltage (min) *	161 V	Cold start	✓
Input operation voltage (max) *	284 V		
Input frequency *	50/60 Hz		
Output operation voltage (min)	220 V		
Output operation voltage (max)	240 V		
Emergency Power Off (EPO)	✗		
Surge protection	✓		
Surge protection features	Fax, Modem, Network, Telephone		
Audible alarm(s)	✓		
Audible alarm modes	Battery replacement		
Ports & interfaces		Design	
AC outlet types	C13 coupler	Form factor *	Tower
Power plug	C14 coupler	Rack capacity	2U
AC outlets quantity	4 AC outlet(s)	Product colour *	Black
USB 2.0 ports quantity	1	LED indicators	Battery replacement
Modem (RJ-11) ports	1		IEC 62040-1, IEC 60950-1, IEC
Ethernet LAN (RJ-45) ports	1		62040-2, CB Report, CE mark, IEC
			61643-1
Battery		Technical details	
Battery technology	Sealed Lead Acid (VRLA)	Harmonized System (HS) code	85078000
		Weight & dimensions	
		Width	81 mm
		Depth	235 mm
		Height	263 mm
		Weight	4.1 kg
		Packaging data	
		Bundled software	Eaton Intelligent Power
		Other features	
		Input connection type	IEC
		Mac compatibility	✓
		Nominal output voltage	220-240 V
		Nominal input voltage	220 V

Other features

Compatible operating systems	Windows 7/Vista/XP/r Mac OS X/r Linux
Overload protection	✓



3553340620836

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 17-JAN-2023. Prints or copies of Information are only valid on the printed Publication date