

## Samsung QH43R Digital signage flat panel 109.2 cm (43") Wi-Fi 700 cd/m<sup>2</sup> 4K Ultra HD Black



**Brand :** Samsung

**Product code:** LH43QHREBGCXEN

**Product name :** QH43R

- Samsung's QHR series displays
- 4K picture quality
- High brightness
- Non-glare
- 24/7 Operation
- 43", New Edge, 60Hz, 3840 x 2160, 700 cd/m<sup>2</sup>, 4000:1, 178/178, 8ms, HDMI, DV, USB, WiFi, Bluetooth

Samsung QH43R Digital signage flat panel 109.2 cm (43") Wi-Fi 700 cd/m<sup>2</sup> 4K Ultra HD Black:

### Time to upscale your display

Samsung's QHR series displays feature best-in-class UHD resolution with unmatched 700 nit brightness, ideal for locations requiring high visibility. The displays also feature intelligent UHD upscaling for stunning picture quality, all in a slim design.

Samsung QH43R. Product design: Digital signage flat panel. Display diagonal: 109.2 cm (43"), Display resolution: 3840 x 2160 pixels, Display brightness: 700 cd/m<sup>2</sup>, HD type: 4K Ultra HD. Wi-Fi. Product colour: Black

Display		Design	
Display diagonal *	109.2 cm (43")	Orientation	Horizontal/Vertical
Display resolution *	3840 x 2160 pixels	Product colour *	Black
Display brightness *	700 cd/m <sup>2</sup>	VESA mounting *	✓
HD type *	4K Ultra HD	Panel mounting interface	200 x 200 mm
Touchscreen *	✗	Performance	
Response time	8 ms	Purpose *	Universal
Contrast ratio (typical)	4000:1	Power	
Dynamic contrast ratio marketing name	Mega Contrast	Power consumption (typical) *	138 W
Viewing angle, horizontal	178°	Power consumption (sleep)	0.5 W
Viewing angle, vertical	178°	AC input voltage	100 - 240 V
Pixel pitch	0.2451 x 0.2451 mm	AC input frequency	50/60 Hz
Horizontal scan range	30 - 135 kHz	Energy efficiency scale	A to G
Vertical scan range	48 - 75 Hz	Weight & dimensions	
Ports & interfaces		Width	967.5 mm
HDMI ports quantity *	2	Depth	48.3 mm
HDMI input ports quantity	2	Height	557.7 mm
DVI port *	✓	Weight	10.7 kg
DisplayPorts quantity *	1	Packaging data	
USB port *	✓	Package width	1095 mm
USB ports quantity	2	Package depth	151 mm
Ethernet LAN *	✓	Package height	676 mm
Wi-Fi *	✓	Package weight	14 kg
Audio		Operational conditions	
Built-in speaker(s) *	✗	Operating temperature (T-T)	0 - 40 °C
Design		Operating relative humidity (H-H)	10 - 80%
Product design *	Digital signage flat panel	Logistics data	
Placement supported *	Indoor	Harmonized System (HS) code	85285210

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 07-MAR-2023. Prints or copies of Information are only valid on the printed Publication date