

## **DELL P Series 27 Monitor - P2722H - 68.6cm (27")**

Brand : DELL Product family: P Series Product code: DELL-P2722H

Product name: 27 Monitor - P2722H - 68.6cm (27")

- 68.6cm (27") Full HD 1920 x 1080 LED IPS
- 16:9, 300cd/m<sup>2</sup>, 1000:1
- USB, VGA, HDMI, DisplayPort

68.6cm (27") Full HD 1920 x 1080 LED IPS, 16:9, 300cd/m<sup>2</sup>, 16.7M, 178°/178°, 1000:1

DELL P Series 27 Monitor - P2722H - 68.6cm (27"):

Stay productive, no matter where you work. Reduce harmful blue light with this sleek 27" FHD monitor featuring ComfortView Plus technology.

DELL P Series 27 Monitor - P2722H - 68.6cm (27"). Display diagonal: 68.6 cm (27"), Display resolution:  $1920 \times 1080 \text{ pixels}$ , HD type: Full HD, Display technology: LCD, Response time: 300 ms, Native aspect ratio: 16:9, Viewing angle, horizontal:  $178^\circ$ , Viewing angle, vertical:  $178^\circ$ . Built-in USB hub, USB hub version: 2.0 / 3.2 Gen 1 (3.1 Gen 1). VESA mounting, Height adjustment. Product colour: Black







Display		Ports & interfaces	
Display diagonal *	68.6 cm (27")	HDCP	✓
Display resolution *	1920 x 1080 pixels	AC (power) in	✓
HD type *	Full HD	Network	
Native aspect ratio *	16:9	Wi-Fi	×
Display technology *	LCD		~
Panel type *	IPS	Ergonomics	
Backlight type	LED	VESA mounting *	1
Touchscreen *	×	Panel mounting interface	100 x 100 mm
Display brightness (typical)	300 cd/m <sup>2</sup>	Cable lock slot *	✓
Response time	300 ms	Height adjustment *	✓
Anti-glare screen	✓	Height adjustment	15 cm
Screen shape *	Flat	Pivot	✓
Supported graphics resolutions	1920 x 1080 (HD 1080)	Pivot angle	-90 - 90°
Supported video modes	480p, 576p, 720p, 1080i, 1080p	Swivelling	✓
Aspect ratio	16:9	Swivel angle range	-45 - 45°
Contrast ratio (typical) *	1000:1	Tilt angle range	-5 - 21°
Maximum refresh rate *	60 Hz	Plug and Play	✓
Viewing angle, horizontal	178°	LED indicators	Power
Viewing angle, vertical	178°	Tilt adjustment	✓
Display number of colours *	16.7 million colours	Power	
Response time (fast)	5 ms	Energy efficiency class (SDR) *	D
Pixel pitch	0.2745 x 0.2745 mm	Energy consumption (SDR) per 1000	
Pixel density	102 ppi	hours *	15 kWh
Horizontal scan range	30 - 83 kHz	Power consumption (typical) *	15 W
Vertical scan range	50 - 76 Hz	Power consumption (standby) *	0.2 W
Viewable size, horizontal	59.8 cm	Power consumption (max)	55 W
Viewable size, vertical	33.6 cm	Power consumption (off)	0.2 W
Viewable size diagonal	68.6 cm	AC input voltage	100 - 240 V
Display diagonal (metric)	68.6 cm	AC input frequency	50/60 Hz

Display		Power	
High Dynamic Range (HDR) supported	×	Power supply type Energy efficiency scale	Internal A to G
Colour depth	6 bit		A 10 0
sRGB coverage (typical)	99%	Operational conditions	
Performance		Operating temperature (T-T) Storage temperature (T-T)	0 - 40 °C -20 - 60 °C
Flicker-free technology	✓	Operating relative humidity (H-H)	10 - 80%
Low Blue Light technology	✓	Storage relative humidity (H-H)	5 - 90%
Multimedia		Operating altitude	0 - 5000 m
Built-in speaker(s) *	×	Non-operating altitude	0 - 12192 m
Built-in camera *	×	Packaging content	
Design		Stand included	✓
Market positioning *	Business	Cables included	AC, DisplayPort, USB
Product colour *	Black	Quick start guide	✓
Front bezel colour	Black	Weight & dimensions	
Detachable stand	✓	Width (with stand)	609.9 mm
Feet colour	Silver	Depth (with stand)	190.1 mm
Heavy metals free	Hg (mercury)	Height (with stand)	384.1 mm
Ports & interfaces		Weight (with stand)	6.77 kg
Built-in USB hub *	✓	Width (without stand)	61 cm
USB hub version	2.0 / 3.2 Gen 1 (3.1 Gen 1)	Depth (without stand)	5.21 cm
USB upstream port type	USB Type-B	Height (without stand)	36 cm
Number of upstream ports	1	Weight (without stand)	4.38 kg
USB Type-A downstream ports	4	Bezel width (side)	6.01 mm
quantity	4	Bezel width (top)	5.99 mm
VGA (D-Sub) ports quantity	1	Bezel width (bottom)	1.73 cm
HDMI *	<b>√</b>	Sustainability	
HDMI ports quantity	1	Sustainability certificates	ENERGY STAR, EPEAT Gold, RoHS
HDMI version	1.4	Doesn't contain	PVC/BFR
DisplayPorts quantity	1	Logistics data	
DisplayPort version	1.2	9	05205210
Headphone out *	×	Harmonized System (HS) code	85285210





5397184505236

5704174604327

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.