EPSON
EXCEED YOUR VISION

# Epson EB-L720U data projector Standard throw projector 7000 ANSI lumens 3LCD WUXGA (1920x1200) White

Brand : Epson

Product name : EB-L720U

Product code: V11HA44040

Epson EB-L720U. Projector brightness: 7000 ANSI lumens, Projection technology: 3LCD, Projector native resolution: WUXGA (1920x1200). Light source type: Laser, Service life of light source: 20000 h, Service life of light source (economic mode): 30000 h. Focus: Manual, Focal length range: 20 - 31.8 mm, Aperture range (F-F): 1.5 - 1.7. Video processing: 10 bit, Video colour modes: Cinema, Dynamic, Presentation, sRGB, DICOM simulation mode. Serial interface type: RS-232C, HDMI connector type: Full-size

Projector

Screen size compatibility *	1270 - 12700 mm (50 - 500")
Projector brightness *	7000 ANSI lumens
Projection technology *	3LCD
Projector native resolution *	WUXGA (1920x1200)
Contrast ratio (typical) *	2500000:1
Native aspect ratio *	16:10
Number of colours	1.07 billion colours
Projector brightness (economic mode)	4900 ANSI lumens
Vertical scan range	192 - 240 Hz
Keystone correction, horizontal	-30 - 30°
Keystone correction, vertical	-30 - 30°
Matrix size	1.7 cm (0.67")

Light source

Light source type *	Laser
Service life of light source *	20000 h
Service life of light source (economic mode)	30000 h

Lens system

Focus *	Manual
Focal length range	20 - 31.8 mm
Aperture range (F-F)	1.5 - 1.7
Zoom capability	✔
Zoom type	Manual
Zoom ratio	1.6:1
Throw ratio	1.35 - 2.20:1
Offset	27%

Video

Full HD *	✔
Video processing	10 bit
Video colour modes	Cinema, Dynamic, Presentation, sRGB, DICOM simulation mode

Ports & interfaces

HDMI connector type	Full-size
HDBaseT port	✔
USB 2.0 ports quantity *	1
USB 2.0 Type-B ports quantity	1

Features

Noise level *	39 dB
Country of origin	China

Multimedia

Built-in speaker(s) *	✔
RMS rated power	10 W
Number of built-in speakers	1

Design

Product type *	Standard throw projector
Product colour *	White
Placement	Ceiling, Desktop, Floor, Wall
Cable lock slot	✔
Cable lock slot type	Kensington

Display

Built-in display *	✖

Power

Power source *	AC
Power consumption (typical) *	345 W
Power consumption (standby) *	0.3 W
Power consumption (economy mode)	258 W
AC input voltage	100-240 V
AC input frequency	50/60 Hz

Software

Software support	via: AMX, Crestron (Network), Control4, Crestron Integrated Partner, Extron IP Link, Extron XTP, AMX Device Discovery, Control4 Simple Device Discovery Protocol

Supplier features

Harmonized System (HS) code	85286200

Operational conditions

Storage temperature (T-T)	-10 - 60 °C
Operating relative humidity (H-H)	20 - 80%
Storage relative humidity (H-H)	10 - 90%

Ports & interfaces

Serial interface type *	RS-232C
PC Audio in	✓
PC Audio out	✓
VGA (D-Sub) ports quantity *	3
HDMI ports quantity *	2
DVI port *	✗

Network

Smart TV *	✗
Ethernet LAN *	✓
Ethernet LAN (RJ-45) ports	1
Ethernet LAN data rates	10,100,1000 Mbit/s
Wi-Fi *	✗

Storage

Card reader integrated *	✗

Features

Interactive *	✗
Noise level (economic mode)	27 dB

Weight & dimensions

Width	440 mm
Depth	122 mm
Height	304 mm
Weight *	7.8 kg
Package width	540 mm
Package depth	530 mm
Package height	210 mm
Package weight	10.8 kg

Packaging content

Remote control included *	✓
Batteries included	✓
Cables included	AC, HDMI
Manual	✓
Warranty card	✓
WLAN adapter included	✓
Packaging content	MB22 ceiling mount
Bundled software	EasyMP Multi PC Projection

Technical details

USB display function	3 in 1: Image / Mouse / Sound
Sustainability certificates	TCO

Logistics data

Quantity per pack	1 pc(s)
Products per pallet	14 pc(s)
Products per pallet (UK)	14 pc(s)

8715946695587