

## iiyama ProLite T1634MC-B8X computer monitor 39.6 cm (15.6") 1920 x 1080 pixels Full HD LED Touchscreen Multi-user Black

**Brand :** iiyama

**Product family:** ProLite

**Product code:** T1634MC-B8X

**Product name :** T1634MC-B8X

iiyama ProLite T1634MC-B8X. Display diagonal: 39.6 cm (15.6"), Display resolution: 1920 x 1080 pixels, HD type: Full HD, Display technology: LED, Response time: 25 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Product colour: Black



Display		Ports & interfaces	
Display diagonal *	39.6 cm (15.6")	USB Touch port	✓
Display resolution *	1920 x 1080 pixels	VGA (D-Sub) ports quantity	1
HD type *	Full HD	HDMI *	✓
Native aspect ratio *	16:9	HDMI ports quantity	1
Display technology *	LED	DisplayPorts quantity	1
Panel type *	IPS	HDCP	✓
Touchscreen *	✓	Ergonomics	
Touchscreen type	Multi-user	Panel mounting interface	100 x 100 mm
Touchscreen technology	Projected capacitive system	Wall mountable	✓
Touch technology	Multi-touch	On Screen Display (OSD)	✓
Number of simultaneous touchpoints	10	On Screen Display (OSD) languages	German, English, Spanish, French, Italian, Japanese
Response time	25 ms	Number of OSD languages	7
Screen shape *	Flat	Tilt adjustment	✓
Contrast ratio (typical) *	700:1	Power	
Maximum refresh rate *	60 Hz	Power consumption (typical) *	18 W
Viewing angle, horizontal	178°	Power consumption (standby) *	1.5 W
Viewing angle, vertical	178°	Power consumption (off)	0.3 W
Display number of colours *	16.2 million colours	Packaging content	
Pixel pitch	0.179 x 0.179 mm	Cables included	AC, DisplayPort, HDMI, USB
Digital horizontal frequency	30 - 84 kHz	Weight & dimensions	
Display diagonal (metric)	39.5 cm	Width (with stand)	381 mm
Surface hardness	7H	Depth (with stand)	202 mm
Display brightness	450 cd/m <sup>2</sup>	Height (with stand)	285.5 mm
Performance		Weight (with stand)	3.6 kg
NVIDIA G-SYNC *	✗	Packaging data	
AMD FreeSync *	✗	Package width	455 mm
Multimedia		Package depth	290 mm
Built-in camera *	✗	Package height	365 mm
Built-in microphone	✗	Package weight	5.8 kg
Design		Logistics data	
Product colour *	Black	Harmonized System (HS) code	85285210
International Protection (IP) code	IP65		
Glass thickness	2.4 mm		

**Other features**

Display viewable area (HxV)	344.2 x 193.6 mm
Placement supported	Horizontal



4948570118335

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 23-FEB-2023. Prints or copies of Information are only valid on the printed Publication date