

Epson TM-m30II-SL (512) 203 x 203 DPI Wired Thermal POS printer

Brand : Epson

Product code: C31CH63512

Product name : TM-m30II-SL (512)

Epson TM-m30II-SL (512). Print technology: Thermal, Type: POS printer, Maximum resolution: 203 x 203 DPI. Maximum roll diameter: 8.3 cm, Supported paper width: 58 mm - 80 mm (Breite), Maximum printing width: 8 cm. Connectivity technology: Wired, USB connector: USB Type-A / USB Type-B. Sound pressure level (printing): 55 dB, Mean time between failures (MTBF): 360000 h, Autocutter durability: 2.2 million cuts. Product colour: White



Printing		Design	
Maximum resolution	203 x 203 DPI	Product colour *	White
Print speed	250 mm/sec	Power	
Print speed (receipt)	250 mm/sec	Power source type *	AC
Printing characters	Text, Graphic, Barcode	Power plug type	Type C
Character sets	ANK	Operational conditions	
Print technology *	Thermal	Operating temperature (T-T)	5 - 45 °C
Type *	POS printer	Storage temperature (T-T)	-20 - 60 °C
Paper handling		Operating relative humidity (H-H)	10 - 90%
Maximum roll diameter	8.3 cm	Storage relative humidity (H-H)	10 - 90%
Supported paper width	58 mm - 80 mm (Breite)	Weight & dimensions	
Maximum printing width	8 cm	Width	140 mm
Ports & interfaces		Depth	214 mm
USB port *	✓	Height	255 mm
USB 2.0 ports quantity	3	Weight	2.9 kg
USB connector	USB Type-A / USB Type-B	Packaging data	
Serial interface *	✗	Quantity per pack	1 pc(s)
Connectivity technology *	Wired	Package width	390 mm
Network		Package depth	410 mm
Ethernet LAN *	✓	Package height	245 mm
Wi-Fi *	✗	Package weight	5.04 kg
Features		Print technology	
Sound pressure level (printing)	55 dB	Column capacity	48/57
Mean time between failures (MTBF)	360000 h	Logistics data	
Cutter	✓	Products per pallet (UK)	32 pc(s)
Half-cutter	✓	Technical details	
Autocutter durability	2.2 million cuts	Font styles	ANK
Tablet charge & sync	✓	Lifetime	17000000 lines
Print head life	150 km	Harmonized System (HS) code	84433210
Country of origin	Philippines	Other features	
Mounting position	Vertical	Buffer size	12 KB
Built-in sensors details	Paper End Sensor, Paper Near End Sensor	Mean cycles between failures (MCBF)	65000000
		Print head life	150.000.000 Impulse



8715946696621

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.