

ZYXEL

## Zyxel POE12-60W 5 Gigabit Ethernet

**Brand :** Zyxel

**Product code:** POE12-60W-GB0101F

**Product name :** POE12-60W

- MultiGig tot 5G PoE++ Injector
  - 60W PoE++ / UPoE 802.3af/at en 802.3bt standaard
  - Single port Powerinjector
  - Eenvoudige installatie voor IEEE 802.3bt compatibele draadloze LAN Aps, IP-videocamera's of IP-telefoons
- Single 1-2.5-5G MultiGig 802.3bt PoE++ Injector [POE12-60W], GB

[Zyxel POE12-60W 5 Gigabit Ethernet:](#)

### Support 5G Blazing-fast Network Speed


PoE12-60W is a Multi-Gigabit PoE injector supporting network speeds of up to 5Gbps. It is allowed to connect powered devices through existing Cat 5e or above cable.

### High PoE Power

PoE12-60W complies with PoE++ providing PoE power up to 60 watts. It offers interoperability and compatibility with other standard-based PoE devices.

### Plug and Play—Ease of Use

PoE12-60W is easy to connect network devices without any configuration. The wall-mount and desktop design accommodate most installations scenarios.



Network		Operational conditions	
Ethernet interface type	5 Gigabit Ethernet	Operating relative humidity (H-H)	5 - 90%
Ethernet LAN data rates	10,100,1000,2500,5000 Mbit/s	Storage temperature (T-T)	-25 - 65 °C
Power over Ethernet (PoE)	✓	Storage relative humidity (H-H)	5 - 90%
Networking standards	IEEE 802.3ab, IEEE 802.3bt, IEEE 802.3bz, IEEE 802.3u	Weight & dimensions	
Features		Width	140 mm
Product colour	Black	Depth	65 mm
LED indicators	✓	Height	38.5 mm
Country of origin	China	Weight	278 g
Ports & interfaces		Packaging data	
Ethernet LAN (RJ-45) ports	2	Package width	168 mm
RJ-45 input ports	1	Package depth	142 mm
RJ-45 output ports	1	Package height	47 mm
		Package weight	1.12 kg
Power		Packaging content	
AC adapter input voltage	100-240 V	Number of products included	1 pc(s)
AC adapter frequency	50/60 Hz	Power cord included	✓
Total Power over Ethernet (PoE) budget	60 W	Logistics data	
Operational conditions		Harmonized System (HS) code	85044090
Operating temperature (T-T)	-10 - 40 °C		
Operating temperature (T-T)	14 - 104 °F		

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 04-MAY-2023. Prints or copies of Information are only valid on the printed Publication date