

DeepCool PM750D power supply unit 750 W 20+4 pin ATX ATX Black

Brand : DeepCool

Product code: R-PM750D-FA0B-UK

Product name : PM750D



750W, ATX12V V2.4, 120mm HYB, 80 PLUS Gold, Non Modular

DeepCool PM750D. Total power: 750 W, AC input voltage: 100 - 240 V, AC input frequency: 47 - 63 Hz. Motherboard power connector: 20+4 pin ATX, Motherboard power cable length: 55 cm, SATA power cable length: 450 mm. Purpose: PC, Power supply unit (PSU) form factor: ATX, 80 PLUS certification: 80 PLUS Gold. Product colour: Black, Cooling type: Active, Fan diameter: 12 cm. Cables included: AC, CPU, PCIe, Peripheral (Molex), SATA

Power		Ports & interfaces	
Total power *	750 W	CPU power connector (4+4 pin)	✓
AC input voltage *	100 - 240 V	CPU power cable length	61 cm
AC input frequency	47 - 63 Hz	ATX power connector (20+4 pin)	✓
Input current	10 A	PCI Express connector	✓
Power Factor Correction (PFC) type	Active	Cabling type	Non-Modular
Combined power (+3.3V)	110 W	Performance	
Combined power (+12V)	750 W	80 PLUS certification *	80 PLUS Gold
Combined power (+5V)	110 W	Supported motherboard form factors	ATX
Combined power (-12V)	3.6 W	Purpose *	PC
Combined power (+5Vsb)	15 W	Power supply unit (PSU) form factor *	ATX
Max output current (+3.3V)	20 A	ATX version	2.4
Max output current (+12V)	62.5 A	Bearing technology	HYB
Max output current (+5V)	20 A	Mean time between failures (MTBF)	100000 h
Max output current (-12V)	0.3 A	Safety	IEC 62368-1
Max output current (+5Vsb)	3 A	Design	
Hold time	16 ms	Product colour	Black
Efficiency	90%	Cooling type	Active
Power protection features	Over current, Over power, Over voltage, Overheating, Short circuit, Under voltage	Fan diameter	12 cm
Ports & interfaces		Number of fans	1 fan(s)
Motherboard power connector *	20+4 pin ATX	Fan location	Top
Motherboard power cable length	55 cm	On/off switch	✓
Number of SATA power connectors	6	Operational conditions	
SATA power cable length	450 mm	Operating temperature (T-T)	0 - 40 °C
Peripheral (Molex) power connectors (4-pin) *	3	Packaging content	
Peripheral (Molex) power cable length	450 mm	Cables included	AC, CPU, PCIe, Peripheral (Molex), SATA
PCI Express power connectors (6+2 pin)	3	Weight & dimensions	
PCI Express power cable length	50 cm	Width	150 mm
		Depth	140 mm
		Height	86 mm
Technical details			
Sustainability certificates		ErP	



6933412709534

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 25-JAN-2023. Prints or copies of Information are only valid on the printed Publication date