

Samsung LH65QBHPLGC/EN Signage Display Digital signage flat panel 165.1 cm (65") LED Wi-Fi 300 cd/m² 4K Ultra HD Black 16/7



Brand : Samsung

Product code: LH65QBHPLGC/EN

Product name : LH65QBHPLGC/EN

- UHD Anti-glare Signage Screen
- 16/7 Usage
- Embedded Media Player (SoC) - Tizen 3.0 OS
- 65", Edge LED, 60Hz, 3840 x 2160, 300 nits, 4700:1, 8ms, HDMI x 2, USB x 2
- Samsung LH65QBHPLGC/EN. Product design: Digital signage flat panel. Display diagonal: 165.1 cm (65"), Display technology: LED, Display resolution: 3840 x 2160 pixels, Display brightness: 300 cd/m², HD type: 4K Ultra HD. Wi-Fi. Operating hours (hours/days): 16/7. Product colour: Black



Display		Design	
LED backlighting type	Edge-LED	Product design *	Digital signage flat panel
Display diagonal *	165.1 cm (65")	Placement supported *	Indoor
Display technology *	LED	Product colour *	Black
Display resolution *	3840 x 2160 pixels	VESA mounting *	✓
Display brightness *	300 cd/m ²	Panel mounting interface	400 x 400 mm
HD type *	4K Ultra HD	Performance	
Response time	8 ms	Operating hours (hours/days)	16/7
Contrast ratio (typical)	4700:1	Power	
Dynamic contrast ratio marketing name	Mega Contrast	Power consumption (typical) *	165 W
Viewing angle, horizontal	178°	Power consumption (standby) *	0.5 W
Viewing angle, vertical	178°	Power consumption (sleep)	0.5 W
Pixel pitch	0.105 x 0.315 mm	Energy efficiency class (SDR)	A
Colour saturation	72%	Energy consumption (SDR) per 1000 hours	178 kWh
Horizontal scan range	30 - 81 kHz	AC input voltage	100 - 240 V
Vertical scan range	48 - 75 Hz	AC input frequency	50 - 60 Hz
Haze rate	2%	Energy efficiency scale	A+++ to D
Ports & interfaces		Weight & dimensions	
HDMI ports quantity *	2	Width	1456.1 mm
DVI port *	✓	Depth	37.5 mm
DVI-D ports quantity	1	Height	835.6 mm
DisplayPorts quantity *	1	Weight	22.8 kg
USB port *	✓	Packaging data	
USB ports quantity	2	Package width	1571 mm
Ethernet LAN *	✓	Package depth	956 mm
Ethernet LAN (RJ-45) ports	1	Package height	212 mm
Wi-Fi *	✓	Package weight	30.8 kg
Audio (L/R) in	1	Operational conditions	
Audio (L/R) out	1	Operating temperature (T-T)	0 - 40 °C
RS-232 interface	✓	Operating relative humidity (H-H)	10 - 80%
RS-232C	✓		
Remote (IR) input	1		

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 16-APR-2024. Prints or copies of Information are only valid on the printed Publication date