

Samsung LH82QPR8BCC Digital signage flat panel 2.08 m (82") LED Wi-Fi 500 cd/m² 8K Ultra HD Black 16/7

Brand : Samsung

Product code: LH82QPR8BCCXEN

Product name : LH82QPR8BCC



- Exceptional 8K resolution with 8K AI Upscaling technology
 - Brilliant picture quality with QLED, 100% color volume and Quantum HDR
 - Minimal and aesthetic design that enhances any customer environment
 82", 7680 x 4320, Direct LED BLU, 500 cd/m², 1850:1, 6 ms, 16/7, Coretex A72 1.7 GHz, 2.5 GB LPDDR4, 8 GB, WiFi, Bluetooth, HDMI, USB, RJ45, RS232, WiFi, IR, 1835.0 x 1055.6 x 34.8 mm
 Samsung LH82QPR8BCC. Product design: Digital signage flat panel. Display diagonal: 2.08 m (82"), Display technology: LED, Display resolution: 7680 x 4320 pixels, Display brightness: 500 cd/m², HD type: 8K Ultra HD. Wi-Fi. Operating hours (hours/days): 16/7. Product colour: Black



Display		Design	
Display diagonal *	2.08 m (82")	Product colour *	Black
Display technology *	LED	VESA mounting *	✓
Display resolution *	7680 x 4320 pixels	Panel mounting interface	600 x 400 mm
Display brightness *	500 cd/m²	Performance	
HD type *	8K Ultra HD	Purpose *	Universal
Touchscreen *	✗	Operating hours (hours/days)	16/7
Native aspect ratio	16:9	HDCP	✓
Response time	6 ms	Power	
Contrast ratio (typical)	1850:1	Power consumption (standby) *	0.5 W
Dynamic contrast ratio marketing name	Mega Contrast	AC input voltage	100 - 240 V
Viewing angle, horizontal	178°	AC input frequency	50 - 60 Hz
Viewing angle, vertical	178°	Computer system	
Display number of colours	10.7 billion colours	Computer system *	✓
Pixel pitch	78.36 x 235.08 mm	Weight & dimensions	
Ports & interfaces		Width	1835 mm
HDMI ports quantity *	4	Depth	34.8 mm
HDMI input ports quantity	4	Height	1055.6 mm
DVI port *	✗	Weight	50 kg
USB port *	✓	Packaging data	
USB ports quantity	3	Package width	2039 mm
Ethernet LAN *	✓	Package depth	260 mm
Wi-Fi *	✓	Package height	1224 mm
Audio (L/R) out	1	Package weight	70 kg
RS-232C	✓	Packaging content	
Audio		Remote control included	✓
Built-in speaker(s) *	✓	Cables included	AC
RMS rated power	60 W	Operational conditions	
Design		Operating temperature (T-T)	0 - 40 °C
Product design *	Digital signage flat panel	Operating relative humidity (H-H)	20 - 95%
Placement supported *	Indoor	Logistics data	
Orientation	Horizontal/Vertical	Harmonized System (HS) code	85285210



8806090339851

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 07-MAY-2024. Prints or copies of Information are only valid on the printed Publication date