



Eaton 5S700IBS uninterruptible power supply (UPS) Line-Interactive 1.5 kVA 900 W 6 AC outlet(s)

Brand : Eaton

Product code: 5S700IBS

Product name : 5S700IBS

5S UPS, Line-interactive, 1500 VA, 900 W, Input C14, Outputs C13, Tower, with BS input cord

Eaton 5S700IBS uninterruptible power supply (UPS) Line-Interactive 1.5 kVA 900 W 6 AC outlet(s):

The Eaton 5S UPS provides cost-effective line-interactive backup power and voltage regulation for small and medium businesses with workstations, desktop PCs, telephone equipment and POS applications. With its compact form factor, the 5S UPS can be utilized as a standalone tower or under a computer monitor.

Eaton 5S700IBS. UPS topology: Line-Interactive, Output power capacity: 1.5 kVA, Output power: 900 W. AC outlet types: C13 coupler, Power plug: C14 coupler, AC outlets quantity: 6 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery capacity: 7 Ah, Battery voltage: 12 V. Form factor: Tower, Product colour: Black, Certification: IEC/EN 62040-1 IEC/EN 62040-2 EAC. Width: 260 mm, Depth: 87 mm, Height: 250 mm



Features		Ports & interfaces	
UPS topology *	Line-Interactive	Serial interface	✗
Output power capacity *	1.5 kVA	Battery	
Output power *	900 W	Battery technology	Sealed Lead Acid (VRLA)
Input operation voltage (min) *	175 V	Battery capacity	7 Ah
Input operation voltage (max) *	275 V	Battery voltage	12 V
Input frequency *	46/70 Hz	Typical backup time at full load	2 min
Output operation voltage (min)	184 V	Automatic battery test	✓
Output operation voltage (max)	276 V	Design	
Output frequency	50/60 Hz	Form factor *	Tower
Automatic Voltage Regulation (AVR)	✓	Product colour *	Black
Number of input phases	1	LED indicators	✓
Number of output phases	1	Certification	IEC/EN 62040-1 IEC/EN 62040-2 EAC
Efficiency	97%	Operational conditions	
Power factor	0.6	Operating temperature (T-T)	0 - 35 °C
Output power factor	0.6	Operating relative humidity (H-H)	0 - 85%
Noise level	25 dB	Operating altitude	0 - 2000 m
Surge protection	✓	Technical details	
Power protection features	Overdischarge	Sustainability compliance	✓
Ports & interfaces		Sustainability certificates	CE
AC outlet types	C13 coupler	Weight & dimensions	
Power plug	C14 coupler	Width	260 mm
AC outlets quantity	6 AC outlet(s)	Depth	87 mm
USB port	✓	Height	250 mm
		Weight	7.1 kg
		Packaging data	
		Cables included	Input power cable, USB cable



3553340620188

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 19-JAN-2023. Prints or copies of Information are only valid on the printed Publication date