



## Eaton 5S1500IBS uninterruptible power supply (UPS) Line-Interactive 0.7 kVA 420 W 8 AC outlet(s)

**Brand :** Eaton

**Product code:** 5S1500IBS

**Product name :** 5S1500IBS



5S UPS, Line-interactive, 700 VA, 420 W, Input: C14, Outputs C13, Tower, with BS input cord

[Eaton 5S1500IBS uninterruptible power supply \(UPS\) Line-Interactive 0.7 kVA 420 W 8 AC outlet\(s\):](#)

The Eaton 5S UPS provides cost-effective line-interactive backup power and voltage regulation for small and medium businesses with workstations, desktop PCs, telephone equipment and POS applications. With its compact form factor, the 5S UPS can be utilized as a standalone tower or under a computer monitor.

Eaton 5S1500IBS. UPS topology: Line-Interactive, Output power capacity: 0.7 kVA, Output power: 420 W. AC outlet types: C13 coupler, Power plug: C14 coupler, AC outlets quantity: 8 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery capacity: 9 Ah, Battery voltage: 12 V. Form factor: Tower, Product colour: Black, Certification: IEC/EN 62040-1 IEC/EN 62040-2 EAC. Width: 382 mm, Depth: 87 mm, Height: 250 mm



Features		Battery	
UPS topology *	Line-Interactive	Battery technology	Sealed Lead Acid (VRLA)
Output power capacity *	0.7 kVA	Battery capacity	9 Ah
Output power *	420 W	Battery voltage	12 V
Input operation voltage (min) *	175 V	Number of batteries supported	2
Input operation voltage (max) *	275 V	Typical backup time at full load	2 min
Input frequency *	46/70 Hz	Automatic battery test	✓
Output operation voltage (min)	184 V	Cold start	✓
Output operation voltage (max)	276 V		
Output frequency	50/60 Hz		
Automatic Voltage Regulation (AVR)	✓		
Number of input phases	1		
Number of output phases	1		
Efficiency	97%		
Power factor	0.6		
Output power factor	0.6		
Noise level	25 dB		
Surge protection	✓		
Surge protection features	Network		
Power protection features	Overdischarge		
Ports & interfaces		Design	
AC outlet types	C13 coupler	Form factor *	Tower
Power plug	C14 coupler	Product colour *	Black
AC outlets quantity	8 AC outlet(s)	LED indicators	✓
USB port	✓	Certification	IEC/EN 62040-1 IEC/EN 62040-2 EAC
USB 2.0 ports quantity	1		
		Operational conditions	
		Operating temperature (T-T)	0 - 35 °C
		Operating relative humidity (H-H)	0 - 85%
		Operating altitude	0 - 2000 m
		Technical details	
		Sustainability compliance	✓
		Sustainability certificates	CE
		Weight & dimensions	
		Width	382 mm
		Depth	87 mm
		Height	250 mm
		Weight	12.5 kg
		Packaging data	
		Cables included	Input power cable, USB cable
		Manual	✓

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 20-JAN-2023. Prints or copies of Information are only valid on the printed Publication date