



Eaton 5SC750IBS uninterruptible power supply (UPS) Line-Interactive 0.75 kVA 525 W 6 AC outlet(s)

Brand : Eaton

Product code: 5SC750IBS

Product name : 5SC750IBS

5SC UPS, Line-interactive, 750 VA, 525 W, Input C14, Outputs 6 x C13, Tower, with BS input cord

[Eaton 5SC750IBS uninterruptible power supply \(UPS\) Line-Interactive 0.75 kVA 525 W 6 AC outlet\(s\):](#)

The Eaton 5SC UPS provides line-interactive, affordable and reliable protection for small business server in any kind of installation constraints. Complementing our range of industry leading UPSs, the 5SC includes an LCD interface for real-time status and measurements, implements manageability solutions compatible with most of IT platforms and provides sinewave output for compatibility with most sensitive IT equipments.

Eaton 5SC750IBS. UPS topology: Line-Interactive, Output power capacity: 0.75 kVA, Output power: 525 W. AC outlet types: C13 coupler, Power plug: C14 coupler, AC outlets quantity: 6 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery capacity: 7 Ah, Battery voltage: 12 V. Form factor: Tower, Product colour: Black, Display type: LCD. Width: 240 mm, Depth: 480 mm, Height: 310 mm



Features		Battery	
UPS topology *	Line-Interactive	Battery technology	Sealed Lead Acid (VRLA)
Output power capacity *	0.75 kVA	Battery capacity	7 Ah
Output power *	525 W	Battery voltage	12 V
Waveform *	Sine	Number of batteries supported	2
Input operation voltage (min) *	184 V	Typical backup time at full load	5 min
Input operation voltage (max) *	276 V	Hot-swap battery	✓
Input frequency *	45/65 Hz	Automatic battery test	✓
Output operation voltage (min)	220 V	Design	
Output operation voltage (max)	240 V	Form factor *	Tower
Output frequency	50/60 Hz	Product colour *	Black
Automatic Voltage Regulation (AVR)	✓	Display type	LCD
Number of input phases	1	Certification	cTUVus IEC/EN 62040-1 UL 1778 IEC/EN 62040-2 EAC
Number of output phases	1	Operational conditions	
Efficiency	96%	Operating relative humidity (H-H)	0 - 90%
Power factor	0.7	Operating altitude	0 - 2000 m
Output power factor	0.7	Technical details	
Noise level	40 dB	Sustainability compliance	✓
Power protection features	Overdischarge	Sustainability certificates	CE
Ports & interfaces		Weight & dimensions	
AC outlet types	C13 coupler	Width	240 mm
Power plug	C14 coupler	Depth	480 mm
AC outlets quantity	6 AC outlet(s)	Height	310 mm
USB port	✓	Weight	11.5 kg
USB 2.0 ports quantity	1	Packaging data	
Serial interface	✓	Rack mount kit	✗
Serial interface type	RS-232	Cables included	Input power cable, Serial, USB cable
Serial ports quantity	1		

Packaging data

Quick installation guide





3553340620409

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 25-JAN-2023. Prints or copies of Information are only valid on the printed Publication date