Eaton 5SC1500IRBS uninterruptible power supply (UPS) Line-Interactive 1.5 kVA 1050 W 9 AC outlet(s)

Brand : Eaton

Product code: 5SC1500IRBS

Product name : 5SC1500IRBS

5SC UPS, Line-interactive, 1500 VA, 1050 W, Input C14, Outputs 8 x C13, Rack, 2U, with BS input cord

Eaton 5SC1500IRBS uninterruptible power supply (UPS) Line-Interactive 1.5 kVA 1050 W 9 AC outlet(s):

The new Eaton 5PX Gen2 UPS provides Enterprise Networks and Edge IT equipment with best-in-class line-interactive power protection maximising IT space and Service Continuity. Eaton 5PX Gen 2 offers powerful tools to remotely monitor, integrate with IT architecture and remotely deploy / maintain large installed base of UPSs.
Eaton 5SC1500IRBS. UPS topology: Line-Interactive, Output power capacity: 1.5 kVA, Output power: 1050 W. AC outlet types: C13 coupler, C19 coupler, Power plug: C20 coupler, AC outlets quantity: 9 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery capacity: 9 Ah, Battery voltage: 12 V. Form factor: Rackmount/Tower, Product colour: Black, Display type: LCD. Width: 522 mm, Depth: 441 mm, Height: 86.2 mm

Features

UPS topology *	Line-Interactive
Output power capacity *	1.5 kVA
Output power *	1050 W
Waveform *	Sine
Input operation voltage (min) *	184 V
Input operation voltage (max) *	276 V
Input frequency *	45/65 Hz
Output operation voltage (min)	220 V
Output operation voltage (max)	240 V
Output frequency	50/60 Hz
Automatic Voltage Regulation (AVR)	✓
Number of input phases	1
Number of output phases	1
Efficiency	97%
Power factor	0.7
Output power factor	0.7
Noise level	40 dB
Power protection features	Overdischarge

Ports & interfaces

AC outlet types	C13 coupler, C19 coupler
Power plug	C20 coupler
AC outlets quantity	9 AC outlet(s)
USB port	✓
USB 2.0 ports quantity	1
USB port type	USB Type-B
Serial interface	✓
Serial interface type	RS-232

Ports & interfaces

Serial ports quantity	1

Battery

Battery technology	Sealed Lead Acid (VRLA)
Battery capacity	9 Ah
Battery voltage	12 V
Number of batteries supported	3
Typical backup time at full load	5 min
Automatic battery test	✓

Design

Form factor *	Rackmount/Tower
Product colour *	Black
Display type	LCD
Certification	TUV IEC/EN 62040-1 IEC/EN 62040-2 EAC cTUVus UL 1778

Operational conditions

Operating relative humidity (H-H)	0 - 90%
Operating altitude	0 - 3000 m

Technical details

Sustainability compliance	✓
Sustainability certificates	CE

Weight & dimensions

Width	522 mm
Depth	441 mm
Height	86.2 mm
Weight	26.9 kg

Packaging data

Rack mount kit	✓
Cables included	Input power cable, USB cable
Quick installation guide	✓

3553340620348