



## Eaton 5SC2200IRTBS uninterruptible power supply (UPS) Line-Interactive 2.2 kVA 1980 W 9 AC outlet(s)

**Brand :** Eaton

**Product code:** 5SC2200IRTBS

**Product name :** 5SC2200IRTBS



5SC UPS, Line-interactive, 2200 VA, 1980 W, Input C20, Outputs 8 x C13 & 1 x C19, Rack/tower, 2U, with BS input cord

[Eaton 5SC2200IRTBS uninterruptible power supply \(UPS\) Line-Interactive 2.2 kVA 1980 W 9 AC outlet\(s\):](#)

The new Eaton 5PX Gen2 UPS provides Enterprise Networks and Edge IT equipment with best-in-class line-interactive power protection maximising IT space and Service Continuity. Eaton 5PX Gen 2 offers powerful tools to remotely monitor, integrate with IT architecture and remotely deploy / maintain large installed base of UPSs.

Eaton 5SC2200IRTBS. UPS topology: Line-Interactive, Output power capacity: 2.2 kVA, Output power: 1980 W. AC outlet types: C13 coupler, C19 coupler, Power plug: C20 coupler, AC outlets quantity: 9 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery capacity: 9 Ah, Battery voltage: 12 V. Form factor: Rackmount/Tower, Product colour: Black, Cable length: 1.8 m. Width: 522 mm, Depth: 441 mm, Height: 86.2 mm



Features		Battery	
UPS topology *	Line-Interactive	Battery technology	Sealed Lead Acid (VRLA)
Output power capacity *	2.2 kVA	Battery capacity	9 Ah
Output power *	1980 W	Battery voltage	12 V
Waveform *	Sine	Number of batteries supported	4
Input operation voltage (min) *	184 V	Typical backup time at full load	2 min
Input operation voltage (max) *	276 V	Automatic battery test	✓
Input frequency *	45/65 Hz	Design	
Output operation voltage (min)	220 V	Form factor *	Rackmount/Tower
Output operation voltage (max)	240 V	Cable length	1.8 m
Output frequency	50/60 Hz	Product colour *	Black
Number of input phases	1	Display type	LCD
Number of output phases	1	Certification	TUV IEC/EN 62040-1 UL 1778 IEC/EN 62040-2 EAC cTUVus
Efficiency	97%	Operational conditions	
Power factor	0.9	Operating relative humidity (H-H)	0 - 90%
Output power factor	0.9	Operating altitude	0 - 3000 m
Noise level	40 dB	Technical details	
Power protection features	Overdischarge	Sustainability compliance	✓
Ports & interfaces		Sustainability certificates	CE
AC outlet types	C13 coupler, C19 coupler	Weight & dimensions	
Power plug	C20 coupler	Width	522 mm
AC outlets quantity	9 AC outlet(s)	Depth	441 mm
USB port	✓	Height	86.2 mm
USB 2.0 ports quantity	1	Weight	26.9 kg
USB port type	USB Type-A	Packaging data	
Serial interface	✓	Rack mount kit	✓
Serial interface type	RS-232	Cables included	Input power cable, Serial, USB cable
Serial ports quantity	1	Quick installation guide	✓



3553340620355

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 30-JAN-2023. Prints or copies of Information are only valid on the printed Publication date