




Eaton 5PX1500IRTNG2BS uninterruptible power supply (UPS) Line-Interactive 1.5 kVA 1500 W 8 AC outlet(s)

Brand : Eaton

Product code: 5PX1500IRTNG2BS

Product name : 5PX1500IRTNG2BS



5PX Gen2 UPS, Line-interactive, 1500 VA, 1500 W, Input C14, Output 8 x C13, Rack/tower, 2U, Network card included, with BS input cord

[Eaton 5PX1500IRTNG2BS uninterruptible power supply \(UPS\) Line-Interactive 1.5 kVA 1500 W 8 AC outlet\(s\):](#)

The new Eaton 5PX Gen2 UPS provides Enterprise Networks and Edge IT equipment with best-in-class line-interactive power protection maximising IT space and Service Continuity. Eaton 5PX Gen 2 offers powerful tools to remotely monitor, integrate with IT architecture and remotely deploy / maintain large installed base of UPSs.

Eaton 5PX1500IRTNG2BS. UPS topology: Line-Interactive, Output power capacity: 1.5 kVA, Output power: 1500 W. AC outlet types: C13 coupler, Power plug: C14 coupler, AC outlets quantity: 8 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery capacity: 9 Ah, Battery voltage: 12 V. Form factor: Rackmount/Tower, Product colour: Black, Silver, Display type: LCD. Width: 498 mm, Depth: 585 mm, Height: 240 mm



Features		Ports & interfaces	
UPS topology *	Line-Interactive	Serial ports quantity	1
Output power capacity *	1.5 kVA	Battery	
Output power *	1500 W	Battery technology	Sealed Lead Acid (VRLA)
Waveform *	Sine	Battery capacity	9 Ah
Input operation voltage (min) *	150 V	Battery voltage	12 V
Input operation voltage (max) *	294 V	Number of batteries supported	4
Input frequency *	47/70 Hz	Automatic battery test	✓
Output operation voltage (min)	200 V	Design	
Output operation voltage (max)	240 V	Form factor *	Rackmount/Tower
Output frequency	50/60 Hz	Product colour *	Black, Silver
Automatic Voltage Regulation (AVR) ✓		Display type	LCD
Number of input phases	1	Certification	IEC/EN 62040-1 IEC/EN 62040-2 IEC/EN 62040-3 UL 1778 CSA 22.2 cTUVus EAC Cm UKCA Ukr KCC
Number of output phases	1	Operational conditions	
Power factor	1	Operating temperature (T-T)	0 - 40 °C
Output power factor	1	Operating relative humidity (H-H)	0 - 90%
Noise level	40 dB	Operating altitude	0 - 3000 m
Power protection features	Overdischarge	Technical details	
Ports & interfaces		Sustainability compliance	✓
AC outlet types	C13 coupler	Sustainability certificates	CE, ENERGY STAR, REACH, RoHS
Power plug	C14 coupler	Weight & dimensions	
AC outlets quantity	8 AC outlet(s)	Width	498 mm
USB port	✓	Depth	585 mm
USB 2.0 ports quantity	1	Height	240 mm
USB port type	USB Type-B	Weight	22.6 kg
Serial interface	✓	Packaging data	
Serial interface type	RS-232	Rack mount kit	✓
		Cables included	Input power cable, Serial, USB cable
		Quick installation guide	✓



3553340620911

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 23-JAN-2023. Prints or copies of Information are only valid on the printed Publication date