



Eaton 5PX3000IRT2UG2BS uninterruptible power supply (UPS) Line-Interactive 3 kVA 3000 W 10 AC outlet(s)

Brand : Eaton

Product code: 5PX3000IRT2UG2BS

Product name : 5PX3000IRT2UG2BS



5PX Gen2 UPS, Line-interactive, 3000 VA, 3000 W, C20 In, 8 x C13 & 2 x C19 Out, Rack/tower, 2U, with BS input cord

[Eaton 5PX3000IRT2UG2BS uninterruptible power supply \(UPS\) Line-Interactive 3 kVA 3000 W 10 AC outlet\(s\):](#)

The new Eaton 5PX Gen2 UPS provides Enterprise Networks and Edge IT equipment with best-in-class line-interactive power protection maximising IT space and Service Continuity. Eaton 5PX Gen 2 offers powerful tools to remotely monitor, integrate with IT architecture and remotely deploy / maintain large installed base of UPSs.

Eaton 5PX3000IRT2UG2BS. UPS topology: Line-Interactive, Output power capacity: 3 kVA, Output power: 3000 W. AC outlet types: C13 coupler, C19 coupler, Power plug: C20 coupler, AC outlets quantity: 10 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery capacity: 9 Ah, Battery voltage: 12 V. Form factor: Rackmount/Tower, Product colour: Black, Silver, Cable length: 1.8 m. Width: 588 mm, Depth: 770 mm, Height: 240 mm

| Features | | Battery | |
|--------------------------------------|--------------------------|-----------------------------------|--|
| UPS topology * | Line-Interactive | Battery technology | Sealed Lead Acid (VRLA) |
| Output power capacity * | 3 kVA | Battery capacity | 9 Ah |
| Output power * | 3000 W | Battery voltage | 12 V |
| Waveform * | Sine | Number of batteries supported | 6 |
| Input operation voltage (min) * | 150 V | Automatic battery test | ✓ |
| Input operation voltage (max) * | 294 V | Design | |
| Input frequency * | 47/70 Hz | Form factor * | Rackmount/Tower |
| Output operation voltage (min) | 200 V | Cable length | 1.8 m |
| Output operation voltage (max) | 240 V | Product colour * | Black, Silver |
| Output frequency | 50/60 Hz | Display type | LCD |
| Automatic Voltage Regulation (AVR) ✓ | | Certification | IEC/EN 62040-1 IEC/EN 62040-2 IEC/EN 62040-3 UL 1778 CSA 22.2 cTUVus EAC Cm UKCA Ukr KCC |
| Number of input phases | 1 | Operational conditions | |
| Number of output phases | 1 | Operating temperature (T-T) | 0 - 40 °C |
| Power factor | 1 | Operating relative humidity (H-H) | 0 - 90% |
| Output power factor | 1 | Storage relative humidity (H-H) | 0 - 90% |
| Noise level | 40 dB | Operating altitude | 0 - 3000 m |
| Power protection features | Overdischarge | Technical details | |
| Ports & interfaces | | Sustainability compliance | ✓ |
| AC outlet types | C13 coupler, C19 coupler | Sustainability certificates | CE, ENERGY STAR, REACH, RoHS |
| Power plug | C20 coupler | Weight & dimensions | |
| AC outlets quantity | 10 AC outlet(s) | Width | 588 mm |
| USB port | ✓ | Depth | 770 mm |
| USB port type | USB Type-B | Height | 240 mm |
| Serial interface | ✓ | Weight | 32.6 kg |
| Serial interface type | RS-232 | Packaging data | |
| Serial ports quantity | 1 | Rack mount kit | ✓ |
| | | Cables included | Input power cable, Serial, USB cable |
| | | Quick installation guide | ✓ |



3553340620881

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 20-JAN-2023. Prints or copies of Information are only valid on the printed Publication date