



Eaton 5PX2200IRTNG2BS uninterruptible power supply (UPS) Line-Interactive 2.2 kVA 2200 W 10 AC outlet(s)

Brand : Eaton

Product code: 5PX2200IRTNG2BS

Product name : 5PX2200IRTNG2BS



5PX Gen2 UPS, Line-interactive, 2200 VA, 2200 W, Input C20, Output 8 x C13 & 2 x C19, Rack/tower, 2U, Network card included, with BS input cord

[Eaton 5PX2200IRTNG2BS uninterruptible power supply \(UPS\) Line-Interactive 2.2 kVA 2200 W 10 AC outlet\(s\):](#)

The new Eaton 5PX Gen2 UPS provides Enterprise Networks and Edge IT equipment with best-in-class line-interactive power protection maximising IT space and Service Continuity. Eaton 5PX Gen 2 offers powerful tools to remotely monitor, integrate with IT architecture and remotely deploy / maintain large installed base of UPSs.

Eaton 5PX2200IRTNG2BS. UPS topology: Line-Interactive, Output power capacity: 2.2 kVA, Output power: 2200 W. AC outlet types: C13 coupler, C19 coupler, Power plug: C20 coupler, AC outlets quantity: 10 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery capacity: 7 Ah, Battery voltage: 12 V. Form factor: Rackmount/Tower, Product colour: Black, Silver, Cable length: 1.8 m. Width: 588 mm, Depth: 770 mm, Height: 240 mm



Features		Ports & interfaces	
UPS topology *	Line-Interactive	Serial ports quantity	1
Output power capacity *	2.2 kVA	Battery	
Output power *	2200 W	Battery technology	Sealed Lead Acid (VRLA)
Waveform *	Sine	Battery capacity	7 Ah
Input operation voltage (min) *	150 V	Battery voltage	12 V
Input operation voltage (max) *	294 V	Number of batteries supported	6
Input frequency *	47/70 Hz	Automatic battery test	✓
Output operation voltage (min)	200 V	Design	
Output operation voltage (max)	240 V	Form factor *	Rackmount/Tower
Output frequency	50/60 Hz	Cable length	1.8 m
Automatic Voltage Regulation (AVR) ✓		Product colour *	Black, Silver
Number of input phases	1	Display type	LCD
Number of output phases	1	Certification	IEC/EN 62040-1 IEC/EN 62040-2 IEC/EN 62040-3 UL 1778 CSA 22.2 cTUVus EAC Cm UKCA Ukr KCC
Power factor	1	Operational conditions	
Output power factor	1	Operating temperature (T-T)	0 - 40 °C
Noise level	40 dB	Operating relative humidity (H-H)	0 - 90%
Power protection features	Overdischarge	Operating altitude	0 - 3000 m
Ports & interfaces		Technical details	
AC outlet types	C13 coupler, C19 coupler	Sustainability compliance	✓
Power plug	C20 coupler	Sustainability certificates	CE, ENERGY STAR, REACH, RoHS
AC outlets quantity	10 AC outlet(s)	Weight & dimensions	
USB port	✓	Width	588 mm
USB 2.0 ports quantity	1	Depth	770 mm
USB port type	USB Type-B	Height	240 mm
Serial interface	✓	Weight	28.7 kg
Serial interface type	RS-232	Packaging data	
		Rack mount kit	✓
		Cables included	Input power cable, Serial, USB cable

Packaging data

Quick installation guide





3553340620928

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 20-JAN-2023. Prints or copies of Information are only valid on the printed Publication date