ASUS ROG STRIX Z690-G GAMING WIFI Intel Z690 LGA 1700 micro ATX

Brand : ASUS Product code: 90MB19G0-M0EAY0

Product name: ROG STRIX Z690-G GAMING WIFI

Intel® Z690 LGA 1700 ATX motherboard with PCle® 5.0, 14+1 DrMos, DDR5 memory support, Two-Way Al Noise Cancelation, Al Overclocking, Al Cooling, Al Networking, WiFi 6E (802.11ax), Intel® 2.5 Gb Ethernet, three M.2 slots with heatsinks, PCle® 4.0 NVMe® SSD support, M.2 backplates, USB 3.2 Gen 2x2 Type-C®, SATA and AURA Sync RGB lighting





Processor manufacturer* Intel® (GA 1700 country) USB 3.2 Gen 2x7 Type-C ports quantity 1 Processor socket * (GA 1700 country) LSB 3.2 Gen 2x7 Type-C ports quantity 1 Compatible processor series* Intel® Celeron®, Intel® Core* ii 7, Inte				
Processor socket* LGA 1700 quantity 1 Compatible processor series* Intel® Core™ 15, Intel® Core™ 17, Intel® Core™ 17, Intel® Core™ 19, Intel® Core™ 17, Intel® Core™ 19, Intel® Core™ 19, Intel® Core™ 17, Intel® Core™ 19, Intel® Core™ 17, Intel® Core™ 19, Intel® Core™ 19, Intel® Core™ 17, Intel® Core™ 19, Intel® Core™ 19, Intel® Core™ 17, Intel® Core™ 19, Intel® Core™ 19, Intel® Core™ 17, Intel® Core™ 19, Intel® Core™ 19, Intel® Core™ 17, Intel® Core™ 19, Intel® Core™ 17, Intel® Core™ 19, Intel® Core™ 19	Processor		Rear panel I/O ports	
Intel® Celeron®, Intel® Core 13, Intel® Core 14, Intel® Core		Intel	, · · ·	1
Intel® Core* State	Processor socket *	LGA 1700	' '	1
Memory LDMI version 2.1 Supported memory types* DDRS-SDRAM DisplayPort version 1.4 Number of memory slots* 4 Headphone outputs 1 Memory channels DIMM Microphone in ✓ Memory channels Dual-channel S/PDIF out port ✓ Supported memory clock speeds 4800,5000,5200,5400,5600,5800,600 Retwork Ethernet LAN ✓ Maximum internal memory 128 GB Ethernet LAN ✓ Maximum internal memory 128 GB Ethernet LAN ✓ Memory derive types 14DD & SSD Wi-Fi * ✓ Storage controllers Top Wi-Fi standard Wi-Fi 6E (802.11ax) Supported storage drive types MD & SSD Wi-Fi standards (802.11n, Wi-Fi 5 (802.11ax) Supported storage drive interface* M.2. SATA Bluetooth ✓ RAID levels Not supported Motherboard chipset * Intel Z690 Rayling processing technology Not supported Audio output channels* 7.1 channels Internal I/O Component for * <td>Compatible processor series *</td> <td></td> <td></td> <td>=</td>	Compatible processor series *			=
Memory DisplayPorts quantity 1 Supported memory types* DDRS-SDRAM DisplayPort version 1.4 Number of memory slots* 4 Headphone outputs 1 Memory slots type DIMM Microphone in ✓ Memory channels Dual-channel S/PDIF out port ✓ Non-ECC ✓ Network Etheret LAN ✓ Supported memory clock speeds 4800,5000,5200,5400,5600,5800,600 Ethernet LAN ✓ Maximum internal memory 128 GB Ethernet LAN ✓ Maximum internal memory √ Wi-Fi Ethernet LAN ✓ Unbuffered memory √ Wi-Fi Ethernet LAN ✓ Storage controllers Top Wi-Fi standard Wi-Fi 6E (802.11ax) 802.11a, 802.11b, 802.11b, Wi-Fi 5 (802.11ax) Storage controllers M.2, SATA Bluetooth ✓ S02.11a, 802.11b, 802.11a, Wi-Fi 5 (802.11ax) Supported storage drive types M.2, SATA Bluetooth ✓ VRAID support square ✓ RAID supported storage drive interfaces * M.2, SATA <td>Compatible processor series *</td> <td></td> <td>1 1 7</td> <td>=</td>	Compatible processor series *		1 1 7	=
Supported memory types* DDR5-SDRAM DisplayPort version 1.4 Number of memory slots* 4 Headphone outputs 1 Memory Slots type DIMM Microphone in ✓ Memory channels Dual-channel S/PDIF out port ✓ Non-ECC V Non-ECC Non-ECC V Supported memory clock speeds M800,5000,5200,5400,5600,5800,6000 Ethernet interface type 2.5 Gigabit Ethernet Maximum internal memory* 128 GB Ethernet interface type 2.5 Gigabit Ethernet Unbufered memory 128 GB Ethernet interface type 2.5 Gigabit Ethernet Storage controllers Top Wi-Fi standard Wi-Fi 6E (802.11ax) Supported storage drive types HDD & SSD Wi-Fi standards 802.11a, 802.11b, 802.11a, Wi-Fi 6E (802.11ax) Supported storage drive interfaces* M.2, SATA Bluetooth ✓ RAID support ✓ Bluetooth ✓ Parallel processing technology Not supported Motherboard chipset * Intel Z690 Supported Audio output channels* Component for*	Mamony			
Number of memory yights No Number of memory yights Number of memory yights Number of memory yights Number of memory yights Number of SATA III connectors Not Sata Air Connectors Not Sat	•	DDDE CDDAM	, , , ,	=
Memory slots type DIMM Microphone in ✓ Memory channels Dual-channel 5/PDIF out port ✓ Non-ECC ✓ Network ✓ Supported memory clock speeds 4800,5000,5200,5400,5600,5800,600 Network ✓ Supported memory 128 GB Ethernet LAN ✓ Maximum internal memory 1 28 GB Ethernet LAN ✓ Unbuffered memory ✓ Wi-Fi ether iterface type 2.5 Gigabit Ethernet Storage controllers Top Wi-Fi standard Wi-Fi 6E (802.11ax) 802.11a, 802.11b, 802.11g, Wi-Fi 6E (802.11ax) Supported storage drive types HDD & SSD Wi-Fi standards (802.11ax), 802.11b, 802.11g, Wi-Fi 6E (802.11ax) Supported storage drive interfaces* M.2, SATA Bluetooth ✓ Supported storage drive interfaces* M.2, SATA Bluetooth ✓ Supported storage drive interfaces* M.2, SATA Interface ✓ Supported storage drive interfaces* M.2, SATA Interface ✓ Supported storage drive interfaces* M.2, SATA Interface ✓				=
Memory channels Dual-channel S/PDIF out port ✓ Non-ECC ✓ Network Supported memory clock speeds 4800,5000,5200,5400,5600,5800,600 Ethernet LAN ✓ Maximum internal memory 128 GB Ethernet interface type 2.5 Gigabit Ethernet Unbuffered memory ✓ Wi-Fi ** ✓ Storage controllers Supported storage drive types HDD & SSD Wi-Fi standards (802.11n,) Wi-Fi 5 (802.11ax) Supported storage drive interfaces ** M.2, SATA Bluetooth ✓ RAID support * Bluetooth ✓ RAID levels 0, 1, 5, 10 Bluetooth ✓ Graphics Features Parallel processing technology Not supported Motherboard chipset * Intel Z690 USB 3.2 Gen 1 (3.1 Gen 1) 2 Audio output channels * 7.1 channels USB 3.2 Gen 1 (3.1 Gen 1) 1 Motherboard chipset family Intel USB 3.2 Gen 2 (3.1 Gen 2) 1 Windows operating systems Windows 10, Windows 11 USB 3.2 Gen 2 (3.1 Gen 2) <td< td=""><td>•</td><td></td><td>•</td><td></td></td<>	•		•	
Non-ECC Supported memory clock speeds		=	•	
Supported memory clock speeds MHz Ethernet LAN Ethernet LAN Ethernet LAN	•			•
Supported memory clock speeds MHz Ethernet LAN Ethernet LAN Waximum internal memory* 128 GB Ethernet interface type Unbuffered memory 128 GB Ethernet interface type Ui-Fi * Yi-Fi * Y		· ·		
Unbuffered memory	Supported memory clock speeds		Ethernet LAN	·
Storage controllers Storage controllers Supported storage drive types HDD & SSD Wi-Fi standard Wi-Fi 6E (802.11ax) 802.11a, 802.11b, 802.11g, Wi-Fi 6E (802.11ax) 802.11a, 802.11b, 802.11g, Wi-Fi 6E (802.11ax) RAID supported storage drive interfaces* M.2, SATA RAID support RAID levels O, 1, 5, 10 Bluetooth Bluetooth version 5.2 Graphics Features Parallel processing technology support* Parallel processing technology support* Not supported Motherboard chipset * Intel Z690 Audio chip Realtek ALC4080 Internal I/O USB 2.0 connectors* 2 Component for * PC Component for * PC USB 3.2 Gen 1 (3.1 Gen 1) connectors* USB 3.2 Gen 2 (3.1 Gen 2) connectors * Intel C690 Motherboard chipset family * Intel Windows operating systems with supported provided form factor * Intel Windows operating systems with supported provided form factor * Intel Windows 10, Windows 11 SUSB 3.2 Gen 2 (3.1 Gen 2) Connectors * PC USB 3.2 Gen 2 (3.1 Gen 2) Connectors * PC Windows operating systems with supported provided form factor * Intel Windows 10, Windows 11 PCI Express x1 (Gen 3.x) slots	Maximum internal memory *	128 GB	• •	•
Supported storage drive types HDD & SSD Wi-Fi standards 802.11a, 802.11b, 802.11b, 802.11g, Wi-Fi Supported storage drive types RAID supported storage drive interfaces* RAID support RAID su	Unbuffered memory	✓		•
Supported storage drive types MDD & SSD Wi-Fi standards (802.11n), Wi-Fi 5 (802.11ac), Wi-Supported storage drive interfaces * M.2, SATA RAID support RAID levels 0, 1, 5, 10 Bluetooth Seatures Features Parallel processing technology support * Mot supported Audio chip Audio chip Realtek ALC4080 Realtek ALC40	Storage controllers		Top Wi-Fi standard	, ,
Supported storage drive interfaces* M.2, SATA RAID support RAID levels O, 1, 5, 10 Bluetooth version Features Parallel processing technology support* Parallel processing technology supported Not supported Motherboard chipset * Audio chip Realtek ALC4080 Internal I/O USB 2.0 connectors * Component for * Com	Supported storage drive types	HDD & SSD	Wi-Fi standards	
RAID support RAID levels 0, 1, 5, 10 Bluetooth version 5.2 Graphics Features Parallel processing technology support* Parallel processing technology support* Not supported Audio chip Audio chip Realtek ALC4080 Internal I/O USB 2.0 connectors* 2 USB 3.2 Gen 1 (3.1 Gen 1) connectors * USB 3.2 Gen 2 (3.1 Gen 2) connectors * USB 3.4 Gen 2 (3.1 Gen 2) connectors * Front panel audio connector ATX Power connector ATX Power connector ATX Power connector ATX Power fan connector ATX Power fan connector AUGHANA PORT AUGHANA PORT AUGHON AUGHAN AUGHAN AUGHON AUGHON		* M.2, SATA	Willistandards	
Features Parallel processing technology support * Not supported Motherboard chipset * Intel Z690 Internal I/O Audio chip Realtek ALC4080 USB 2.0 connectors * 2 Audio output channels * 7.1 channels USB 3.2 Gen 1 (3.1 Gen 1) connectors * 1 Motherboard form factor * micro ATX USB 3.2 Gen 2 (3.1 Gen 2) connectors * 1 Windows operating systems supported Windows 10, Windows 11 Vumber of SATA III connectors * 6 Expansion slots Front panel audio connector ✓ PCI Express x1 (Gen 3.x) slots and the properties of Gen 4.x) slots and the properties of Gen 4.x slots and the properties of Mumber of M.2 (M) slots and the properties of Mumber of M.2 (M) slots and the properties of Gen 4.x slots a	RAID support	✓	Bluetooth	✓
Parallel processing technology support * Mot supported Audio chipset * Intel Z690 Internal I/O Audio output channels * 7.1 channels USB 2.0 connectors * 2 USB 3.2 Gen 1 (3.1 Gen 1) connectors * 1 Component for * PC Motherboard chipset family * Intel USB 3.2 Gen 2 (3.1 Gen 2) connectors * 2 Number of SATA III connectors * 6 Front panel audio connector	RAID levels	0, 1, 5, 10	Bluetooth version	5.2
Not supportedAudio chipRealtek ALC4080Internal I/OAudio output channels *7.1 channelsUSB 2.0 connectors *2Component for *PCUSB 3.2 Gen 1 (3.1 Gen 1) connectors *1Motherboard form factor *micro ATXUSB 3.2 Gen 2 (3.1 Gen 2) connectors *1Windows operating systems supportedWindows 10, Windows 11Number of SATA III connectors *6Expansion slotsFront panel audio connector✓PCI Express x1 (Gen 3.x) slots PCI Express x16 (Gen 4.x) slots Number of M.2 (M) slots1POU fan connector✓Number of M.2 (M) slots3CPU fan connector✓BIOSNumber of (Nolex) power connectors (4-pin)BIOS type *UEFI AMI EBIOS memory size	Graphics		Features	
Not supportedAudio chipRealtek ALC4080Internal I/OAudio output channels*7.1 channelsUSB 2.0 connectors*2Component for *PCUSB 3.2 Gen 1 (3.1 Gen 1) connectors*1Motherboard form factor *micro ATXUSB 3.2 Gen 2 (3.1 Gen 2) connectors *1Windows operating systems supportedWindows 10, Windows 11Number of SATA III connectors *6Expansion slotsFront panel audio connector✓PCI Express x1 (Gen 3.x) slots PCI Express x16 (Gen 4.x) slots Number of M.2 (M) slots1Power fan connector✓Number of M.2 (M) slots3CPU fan connector✓BIOSNumber of (Molex) power connectors (4-pin)BIOS type *UEFI AMI BIOS memory size	Parallel processing technology	Notes and all	Motherboard chipset *	Intel Z690
USB 2.0 connectors * 2 USB 3.2 Gen 1 (3.1 Gen 1) connectors * 1 USB 3.2 Gen 2 (3.1 Gen 2) connectors * 1 USB 3.2 Gen 2 (3.1 Gen 2) connectors * 6 Vindows operating systems supported Number of SATA III connectors * 6 Front panel audio connector		Not supported	Audio chip	Realtek ALC4080
USB 3.2 Gen 1 (3.1 Gen 1) connectors * Intel Motherboard form factor * Intel Motherboard chipset family * Intel USB 3.2 Gen 2 (3.1 Gen 2) connectors * Intel Windows operating systems supported Windows 10, Windows 11 windows 11 windows 11 windows 12 windows 13 windows 14 windows 15 windows 16 windows 16 windows 16 windows 17 windows 18 windows 19 windows 19 windows 19 windows 19 windows 19 windows 19 windows 10 windows 11 windows 19 windows 10 windows 11 windows 10 windows 11 windows 10 windows 10 windows 10 windows 10 windows 10 windows 11 windows 10 wind	Internal I/O		Audio output channels *	7.1 channels
USB 3.2 Gen 1 (3.1 Gen 1) connectors * USB 3.2 Gen 2 (3.1 Gen 2) connectors * Number of SATA III connectors Front panel audio connector ATX Power connector (24-pin) Power fan connector CPU fan connector Number of chassis fan connectors Power for chassis fan connectors Power for chassis fan connectors ATX Power (Molex) power connector (4-pin) Power for chassis fan connector BIOS BIOS Motherboard form factor * Micro ATX Motherboard form factor * Micro ATX Motherboard form factor * Micro ATX Micro ATX Motherboard chipset family * Intel Intel Mindows 10, Windows 11 PCI Express x1 (Gen 3.x) slots 1 PCI Express x1 (Gen 3.x) slots 1 Number of M.2 (M) slots 3 BIOS UEFI AMI BIOS memory size 256 Mbit	USB 2.0 connectors *	2	Component for *	PC
connectors * Intel USB 3.2 Gen 2 (3.1 Gen 2) connectors * Intel Windows operating systems supported Number of SATA III connectors * 6 Front panel audio connector ATX Power connector (24-pin) Power fan connector CPU fan connector Number of chassis fan connectors POI Express x1 (Gen 3.x) slots POI Express x16 (Gen 4.x) slots POI fan connector Number of chassis fan connector BIOS BIOS Windows 10, Windows 11 POI Express x1 (Gen 3.x) slots POI Express x16 (Gen 4.x)			Motherboard form factor *	micro ATX
Number of SATA III connectors * 6 Number of SATA III connectors * 6 Front panel audio connector	, , ,	1	Motherboard chipset family *	Intel
Front panel audio connector ATX Power connector (24-pin) POI Express x1 (Gen 3.x) slots POI Express x16 (Gen 4.x) slots POI Express x16 (Gen 4.x) slots Number of M.2 (M) slots Power fan connector Number of chassis fan connectors Peripheral (Molex) power connectors Peripheral (Molex) power connectors Peripheral (Molex) power connectors BIOS BIOS type * UEFI AMI BIOS memory size 256 Mbit		1	, ,	Windows 10, Windows 11
Front panel audio connector ATX Power connector (24-pin) POI Express x1 (Gen 3.x) slots POI Express x1 (Gen 3.x) slots POI Express x1 (Gen 3.x) slots POI Express x1 (Gen 4.x) slots Number of M.2 (M) slots BIOS Peripheral (Molex) power connectors (4-pin) POI Express x1 (Gen 3.x) slots 1 Number of M.2 (M) slots BIOS BIOS BIOS BIOS type * BIOS memory size DEFI AMI BIOS memory size	Number of SATA III connectors *	6	Expansion slots	
ATX Power connector (24-pin) Power fan connector CPU fan connector Number of chassis fan connectors PCI Express x16 (Gen 4.x) slots Number of M.2 (M) slots BIOS BIOS BIOS BIOS type * UEFI AMI BIOS memory size 256 Mbit	Front panel audio connector	✓	•	1
Power fan connector CPU fan connector Number of chassis fan connectors Peripheral (Molex) power connectors (4-pin) Number of chassis fan connectors BIOS BIOS BIOS type * UEFI AMI BIOS memory size 256 Mbit	ATX Power connector (24-pin)	✓	•	
CPU fan connector Number of chassis fan connectors Peripheral (Molex) power connectors (4-pin) RIOS BIOS BIOS BIOS UEFI AMI BIOS memory size 256 Mbit	Power fan connector	✓	•	
Peripheral (Molex) power connectors (4-pin) BIOS type * UEFI AMI BIOS memory size 256 Mbit		✓	` '	
connectors (4-pin) BIOS memory size 256 Mbit	Number of chassis fan connectors	3		
EPS power connector (8-pin) ✓		1	· ·	
	EPS power connector (8-pin)	✓		



4711081455417

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.