D-Link

D-Link DEM-431XT network transceiver module Fiber optic 10000 Mbit/s SFP+ 850 nm

Brand: D-Link Product code: DEM-431XT

Product name: DEM-431XT

D-Link DEM-431XT. SFP transceiver type: Fiber optic, Maximum data transfer rate: 10000 Mbit/s, Interface type: SFP+. Safety: UL, TUV, CDRH, Certification: CE, FCC, VCCI, C-Tick. Maximum voltage: 3.3 V, Maximum current: 300 A. Width: 14.8 mm, Depth: 11.8 mm, Height: 56.5 mm. Package width: 74 mm,


Package depth: 131 mm, Package height: 49 mm





Performance		Weight & dimensions	
SFP transceiver type * Maximum data transfer rate * Interface type *	Fiber optic 10000 Mbit/s SFP+	Depth Height Weight	11.8 mm 56.5 mm 18 g
Multi-mode fiber (MMF) supported Fiber optic connector Fiber cable diameters supported (core/cladding) Maximum transfer distance Wavelength Tx power (min) Tx power (max) Rx power (min) Rx power (max) Networking standards	LC 50/125,62.5/125 μm 300 m 850 nm -6.5 dBmW -1 dBmW -11.1 dBmW -1 dBmW	Packaging data Package width Package depth Package height Package weight Technical details Sustainability certificates Logistics data Shipping (inner) case length	74 mm 131 mm 49 mm 64 g RoHS
Harmonized System (HS) code Features Safety Certification	85369010 UL, TUV, CDRH CE, FCC, VCCI, C-Tick	Shipping (inner) case width 26 cm Shipping (inner) case height 31 cm Shipping (inner) case net weight 3.2 kg Products per shipping (inner) case 50 pc(s) Pallet gross weight (air) 272 kg Master (outer) cases per pallet (air) 60 pc(s) Products per pallet (air) 3000 pc(s) Pallet gross length 102 cm Pallet gross width 122 cm Pallet height (air) 199 cm	31 cm 3.2 kg 50 pc(s)
Power Maximum voltage Maximum current Operational conditions	3.3 V 300 A		3000 pc(s) 102 cm 122 cm
Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Weight & dimensions Width	0 - 70 °C -40 - 85 °C 5 - 85% 5 - 95%	Pallet gross weight (sea) Master (outer) cases per pallet (sea) Products per pallet (sea) Pallet height (sea) Shipping (inner) case gross weight	272 kg 60 pc(s) 3000 pc(s) 199 cm 4.2 kg











Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.