# Intel Core i3-12100 processor 12 MB Smart Cache Box

Brand : Intel   **Product family:** Core   **Product code:** BX8071512100

Product name : i3-12100

Boxed Intel® Core™ i3-12100 Processor (12M Cache, up to 4.30 GHz) FC-LGA16A
Intel Core i3-12100. Processor family: Intel® Core™ i3, Processor socket: LGA 1700, Processor
manufacturer: Intel. Memory channels: Dual-channel, Maximum internal memory supported by
processor: 128 GB, Memory types supported by processor: DDR4-SDRAM, DDR5-SDRAM. On-board
graphics card model: Intel UHD Graphics 730, On-board graphics card outputs supported: Embedded
DisplayPort (eDP) 1.4b, DisplayPort 1.4a, HDMI 2.1, On-board graphics card base frequency: 300 MHz.
Market segment: Desktop, Use conditions: PC/Client/Tablet, PCI Express slots version: 5.0, 4.0. Package
type: Retail box

Processor

Processor manufacturer *	Intel
Processor generation	12th gen Intel® Core™ i3
Processor model *	i3-12100
Processor family *	Intel® Core™ i3
Processor cores *	4
Processor socket *	LGA 1700
Processor threads	8
Processor operating modes *	64-bit
Performance cores	4
Processor boost frequency	4.3 GHz
Performance-core boost frequency	4.3 GHz
Performance-core base frequency	3.3 GHz
Processor cache	12 MB
Processor cache type	Smart Cache
Box *	✔
Processor base power	60 W
Maximum turbo power	89 W
Bus type	DMI4
Maximum number of DMI lanes	8
Memory bandwidth supported by processor (max)	76.8 GB/s
Processor codename	Alder Lake

Memory

Maximum internal memory supported by processor	128 GB
Memory types supported by processor	DDR4-SDRAM, DDR5-SDRAM
Memory channels *	Dual-channel
Memory bandwidth (max)	76.8 GB/s

Graphics

On-board graphics card *	✔
Discrete graphics card *	✘
On-board graphics card model *	Intel UHD Graphics 730
On-board graphics card outputs supported	Embedded DisplayPort (eDP) 1.4b, DisplayPort 1.4a, HDMI 2.1
On-board graphics card base frequency	300 MHz
On-board graphics card dynamic frequency (max)	1400 MHz
Number of displays supported (on-board graphics)	4
On-board graphics card DirectX version	12.0

Features

Maximum number of PCI Express lanes	20
PCI Express slots version	5.0, 4.0
PCI Express configurations	1x16+1x4, 2x8+1x4
Supported instruction sets	SSE4.1, SSE4.2, AVX 2.0
Scalability	1S
CPU configuration (max)	1
Embedded options available	✘
Direct Media Interface (DMI) Revision	4.0
Harmonized System (HS) code	85423119
Export Control Classification Number (ECCN)	5A992CN3
Commodity Classification Automated Tracking System (CCATS)	G167599

Processor special features

Intel® Hyper Threading Technology (Intel® HT Technology)	✔
Intel® Turbo Boost Technology	2.0
Intel® Quick Sync Video Technology	✔
Intel® Clear Video HD Technology (Intel® CVT HD)	✔
Intel® AES New Instructions (Intel® AES-NI)	✔
Enhanced Intel SpeedStep Technology	✔
Intel® Speed Shift Technology	✔
Intel® Gaussian & Neural Accelerator (Intel® GNA) 3.0	✔
Intel® Control-flow Enforcement Technology (CET)	✔
Intel® Thread Director	✘
Intel VT-x with Extended Page Tables (EPT)	✔
Intel® Secure Key	✔
Intel® OS Guard	✔
Intel 64	✔
Intel Virtualization Technology (VT-x)	✔
Intel Virtualization Technology for Directed I/O (VT-d)	✔
Intel Turbo Boost Max Technology 3.0	✘
Intel® Optane™ Memory Ready	✔
Intel® Boot Guard	✔

Graphics

On-board graphics card OpenGL version	4.5
On-board graphics card maximum resolution (DisplayPort)	7680 x 4320 pixels
On-board graphics card maximum resolution (eDP - Integrated Flat Panel)	5120 x 3200 pixels
On-board graphics card maximum resolution (HDMI)	4096 x 2160 pixels
On-board graphics card refresh rate at maximum resolution (DisplayPort)	60 Hz
On-board graphics card refresh rate at maximum resolution (eDP - Integrated Flat Panel)	120 Hz
On-board graphics card refresh rate at maximum resolution (HDMI)	60 Hz
On-board graphics card ID	0x4692
Discrete graphics card model *	Not available
Number of execution units	24
Multi-Format Codec Engines	1

Features

Execute Disable Bit	✔
Idle States	✔
Thermal Monitoring Technologies	✔
Market segment	Desktop
Use conditions	PC/Client/Tablet

Processor special features

Intel® Deep Learning Boost (Intel® DL Boost)	✔
Intel® Volume Management Device (VMD)	✔
Mode-based Execute Control (MBE)	✔
Intel® Standard Manageability (ISM)	✔
Intel® Threat Detection Technology (TDT)	✔

Operational conditions

Tjunction	100 °C

Technical details

OpenCL version	2.1
Launch date	Q1'22
Status	Launched

Packaging data

Package type	Retail box

Weight & dimensions

Processor package size	45 x 37.5 mm

Other features

Maximum internal memory	128 GB
Graphics output	eDP 1.4b, DP 1.4a, HDMI 2.1

5032037238458

5032037238465

0735858503877

735858503877