## ASUS WS X299 SAGE/10G Intel® X299 LGA 2066 SSI CEB

Brand : ASUS

Product code: 90SW00H0-M0EAY0

Product name : WS X299 SAGE/10G

WS X299 SAGE/10G, Intel X299, LGA 2066, 8x DDR4 DIMM, 7x PCIe 3.0 x16, 10G LAN, USB 3.1, U.2, M.2, CEB, 305x267 mm

ASUS WS X299 SAGE/10G. Processor manufacturer: Intel, Processor socket: LGA 2066. Supported memory types: DDR4-SDRAM, Maximum internal memory: 512 GB, Memory channels: Quad-channel. Supported storage drive interfaces: SATA III, RAID levels: 0, 1, 5, 10. Parallel processing technology support: 4-Way CrossFireX, 4-Way SLI. Ethernet interface type: 10 Gigabit Ethernet, LAN controller: Intel® X550-AT2





Processor		Rear panel I/O ports	
Processor manufacturer * Processor socket *	Intel LGA 2066	USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity *	1
Memory		USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity *	1
Supported memory types * Number of memory slots * Memory channels	DDR4-SDRAM 8 Ouad-channel	Ethernet LAN (RJ-45) ports *	2
		Network	
Supported memory clock speeds Maximum internal memory *	2133,2400,2666 MHz 512 GB	Ethernet LAN Ethernet interface type LAN controller	✓ 10 Gigabit Ethernet Intel® X550-AT2
Storage controllers		Wi-Fi *	x
Supported storage drive interfaces		Features	
RAID support RAID levels	✓ 0, 1, 5, 10	Motherboard chipset * Audio chip	Intel® X299 Realtek ALC S1220A
Graphics		Audio output channels *	7.1 channels
Parallel processing technology support *	4-Way CrossFireX, 4-Way SLI	Component for * Motherboard form factor *	Workstation SSI CEB
Internal I/O		Motherboard chipset family *	Intel
USB 3.2 Gen 1 (3.1 Gen 1) connectors *	1	Harmonized System (HS) code Certification	84733020 CE
USB 3.2 Gen 2 (3.1 Gen 2) connectors *	1	Expansion slots	
Number of SATA III connectors * ATX Power connector (24-pin)	8	PCI Express x16 (Gen 3.x) slots Number of M.2 (M) slots	7 2
Number of EATX power connectors	1	BIOS	
Number of chassis fan connectors 2	2	BIOS type * Clear CMOS button	UEFI ✓
EPS power connector (8-pin) Number of COM connectors	1	Operational conditions	
TPM connector	1	Storage temperature (T-T)	-40 - 70 °C
Rear panel I/O ports		Operating temperature (T-T)	10 - 35 °C
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity *	4	Operating relative humidity (H-H) 20 - 90%	

Weight & dimensions			
Width	305 mm		
Depth	267 mm		
Height	287 mm		
Packaging content			
Cables included	SATA		
Other features			
Weight	2.2 kg		





753459461204

0753459461204



4712900952001

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.