


ASUS P12R-M Intel C252 LGA 1200 (Socket H5) micro ATX

Brand : ASUS

Product code: 90SB09X0-M1UAY0

Product name : P12R-M

- Ideal for remote office/branch office (ROBO) use and everyday business environments
 - Powered by eight-core Intel® Xeon E-2300-series processor with support for up to 95 W TDP
 - Flexible expandability with six native SATA HDDs and two PCI Express 4.0 slots
 - Dual Intel I210AT Gigabit Ethernet with teaming support
 - One M.2 for up to 32 Gbps performance for faster OS booting
 - HDMI 1.4 support for high-resolution display maintenance and monitoring
 - Onboard ASUS ASMB10-iKVM with ASPEED AST2600 controller for out-of-band management
 - Integrated PFR FPGA as the platform Root-of-Trust solution for firmware resiliency
- LGA1200, Intel C252, max 128GB UDIMM, U ATX, 6 x SATA 6Gb/s



Processor		Rear panel I/O ports	
Processor manufacturer *	Intel	USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity *	2
Processor socket *	LGA 1200 (Socket H5)	Ethernet LAN (RJ-45) ports *	2
Compatible processor series *	Intel® Pentium®, Intel Xeon E	VGA (D-Sub) ports quantity *	1
Memory		HDMI ports quantity *	1
Supported memory types *	DDR4-SDRAM	Network	
Number of memory slots *	4	Ethernet LAN	✓
Memory slots type	DIMM	LAN controller	Intel® I210-AT
Memory channels	Dual-channel	Wi-Fi *	✗
Supported memory clock speeds	2666,2933,3200 MHz	Features	
Maximum internal memory *	128 GB	Motherboard chipset *	Intel C252
Supported memory module capacities	4GB, 8GB, 16GB, 32GB	Component for *	Server
Storage controllers		Motherboard form factor *	micro ATX
Supported storage drive interfaces *	M.2, SATA III	Motherboard chipset family *	Intel
Graphics		Expansion slots	
Graphics card family	ASPEED	PCI Express x16 (Gen 4.x) slots	1
Graphics card	AST2600	Number of M.2 (M) slots	1
On-board graphics card memory	64 MB	Operational conditions	
Internal I/O		Storage temperature (T-T)	-40 - 70 °C
USB 3.2 Gen 2 (3.1 Gen 2) connectors *	2	Operating temperature (T-T)	10 - 50 °C
Number of SATA III connectors *	6	Storage relative humidity (H-H)	20 - 90%
ATX Power connector (24-pin)	✓	Logistics data	
EPS power connector (8-pin)	✓	Harmonized System (HS) code	84733020
Serial port headers	1	Packaging data	
		Package weight	1.3 kg
		Weight & dimensions	
		Width	244 mm
		Depth	244 mm



4711081384571



4711081684749

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.