Zyxel GS1100-10HP v2 Unmanaged Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Black

Brand: Zyxel **Product code**: GS1100-10HP-GB0102F

Product name: GS1100-10HP v2

8-port GbE Unmanaged PoE Switch with GbE Uplink, GB

Zyxel GS1100-10HP v2. Switch type: Unmanaged. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 8. MAC address table: 8000 entries, Switching capacity: 20 Gbit/s. Networking standards: IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3at, IEEE 802.3at, IEEE 802.3at, IEEE 802.3u, IEEE.... DC input voltage: 54 V. Power connector: DC-in jack. Power over Ethernet (PoE). Wall mountable







Management features		Power over Ethernet (PoE)	
Switch type *	Unmanaged	Power over Ethernet (PoE) *	✓
Ports & interfaces		Power over Ethernet (PoE) ports quantity	8
Basic switching RJ-45 Ethernet ports quantity *	C	Total Power over Ethernet (PoE) budget	130 W
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Operational conditions	
SFP module slots quantity	2	Operating temperature (T-T)	0 - 50 °C
Power connector	DC-in jack	Storage temperature (T-T)	-40 - 70 °C
Network		Operating relative humidity (H-H)	10 - 90%
	IEEE 802.1p, IEEE 802.3, IEEE	Storage relative humidity (H-H)	10 - 95%
Networking standards *	802.3ab, IEEE 802.3af, IEEE	Heat dissipation	89 BTU/h
Networking Standards	802.3at, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Weight & dimensions	
10G support *	×	Width	250 mm
Auto MDI/MDI-X	1	Depth	104 mm
Ethernet LAN data rates	100,1000 Mbit/s	Height	27 mm
Data transmission		Weight	730 g
Switching capacity *	20 Gbit/s	Packaging data	
Forwarding rate	14.88 Mpps	Package width	228 mm
MAC address table *	8000 entries	Package depth	304 mm
Jumbo frames support	✓	Package height	67 mm
Jumbo frames	9000	Package weight	1.97 kg
Packet buffer memory	0.256 MB	Sustainability	
Design		Sustainability compliance	✓
Product colour	Black	Sustainability certificates	RoHS
LED indicators	✓	Logistics data	
Wall mountable	✓	Master (outer) case width	323 mm
Country of origin	China	Master (outer) case length	558 mm

Performance Logistics data Mean time between failures (MTBF) 1000070 h 275 mm Master (outer) case height 85176990 Harmonized System (HS) code Power Master (outer) case gross weight 13.7 kg Power source * AC/DC Products per master (outer) case 8 pc(s) Power supply included * AC input voltage 100 - 240 V AC input frequency 50/60 Hz

DC input voltage

Power consumption (max)

54 V

156.1 W

