

Allied Telesis AT-TQ6602 GEN2-00 wireless access point White Power over Ethernet (PoE)



Brand : Allied Telesis

Product code: AT-TQ6602 GEN2-00

Product name : AT-TQ6602 GEN2-00

Enterprise-Class Wi-Fi 6 AP with 2 radios (4x4 2.4GHZ and 8x8 5GHz) and embedded antenna

[Allied Telesis AT-TQ6602 GEN2-00 wireless access point White Power over Ethernet \(PoE\):](#)

The Allied Telesis Enterprise-class TQ6602 GEN2 hybrid wireless AP features Wi-Fi 6 technology with 4 spatial streams (4x4) to deliver a raw capacity of 3.55 Gigabits. Multi-Gigabit uplink ports ensure maximum wireless network performance and eliminate bottlenecks.

Allied Telesis AT-TQ6602 GEN2-00. Networking standards: IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11e, IEEE 802.11g, IEEE 802.11i, IEEE 802.11k, IEEE 802.11n, IEEE 802.11r, IEEE 802.11v, IEEE 802.11X, IEEE 802.1Q, IEEE 802.3, IEEE 802.3ab, IEEE 802.3at, IEEE 802.3bz, IEEE 802.3u, IEEE 802.3x. MIMO type: Multi User MIMO. Security algorithms: 64-bit WEP, 128-bit WEP, WPA, WPA2, WPA2-AES, WPA2-CCMP, WPA3. AC input voltage: 100 - 240 V, Power consumption (typical): 15 W, Power consumption (max): 19 W. Product colour: White, Cable lock slot type: Kensington. Antenna type: Internal, Antenna direction type: Omni-directional, Antenna gain level (max): 5.93 dBi

Features		Design	
2.4 GHz *	✓	Cable lock slot	✓
5 GHz *	✓	Cable lock slot type	Kensington
6 GHz *	✗	Antenna	
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11e, IEEE 802.11g, IEEE 802.11i, IEEE 802.11k, IEEE 802.11n, IEEE 802.11r, IEEE 802.11v, IEEE 802.1AX, IEEE 802.1Q, IEEE 802.3, IEEE 802.3ab, IEEE 802.3at, IEEE 802.3bz, IEEE 802.3u, IEEE 802.3x	Antenna type *	Internal
		Antenna direction type	Omni-directional
		Antenna gain level (max)	5.93 dBi
		Weight & dimensions	
		Width	200 mm
MIMO	✓	Depth	240 mm
MIMO type	Multi User MIMO	Height	45 mm
		Weight	1.2 kg
Security		Operational conditions	
Security algorithms *	64-bit WEP, 128-bit WEP, WPA, WPA2, WPA2-AES, WPA2-CCMP, WPA3	Operating relative humidity (H-H)	5 - 90%
		Operating temperature (T-T)	0 - 50 °C
		Storage temperature (T-T)	-25 - 70 °C
		Storage relative humidity (H-H)	5 - 95%
Protocols			
DHCP client	✓		
Power			
Power over Ethernet (PoE) *	✓		
AC input voltage	100 - 240 V		
Power consumption (typical)	15 W		
Power consumption (max)	19 W		
Design			
Product colour *	White		



0767035224619



767035224619

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.