Zyxel GS1915-8 Managed L2 Gigabit Ethernet (10/100/1000) Black

Brand : Zyxel **Product code:** GS1915-8-GB0101F

Product name: GS1915-8

GS1915-8 - 8-port GbE Smart Managed Switch

Zyxel GS1915-8. Switch type: Managed, Switch layer: L2. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 8. Full duplex. MAC address table: 8000 entries, Switching capacity: 16 Gbit/s. Networking standards: IEEE 802.1Q, IEEE 802.1s, IEEE 802.1x, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az,.... Power connector: AC-in jack





Management features		Protocols		
Switch type *	Managed L2	Management protocols	SNMP v1,v2,v3, RMON (1,2,3,9)	
Switch layer		Design		
Quality of Service (QoS) support	√	Product colour	Black	
Web-based management	1	LED indicators	✓	
System event log	✓ RFC 1213 MIB II, RFC 2819, RFC	Electromagnetic compatibility	LVD EN60950-1, BSMI CNS14336-1	
MIB support	1215, RFC 1493	Certification	CE, FCC, C-Tick, Class A, Class B, BSMI CNS13438	
Ports & interfaces		Performance		
Basic switching RJ-45 Ethernet ports quantity *	8	Mean time between failures (MTBF)	1144461 h	
Basic switching RJ-45 Ethernet ports	Gigabit Ethernet (10/100/1000)	Power		
type * Gigabit Ethernet (copper) ports		Power source *	AC	
quantity	8	AC input voltage	220 - 240 V	
Power connector	AC-in jack	AC input frequency	50/60 Hz	
Network		Power consumption (max)	4.7 W	
Networking standards *	IEEE 802.1Q, IEEE 802.1s, IEEE 802.1x, IEEE 802.3ab, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x	Power over Ethernet (PoE)		
		Power over Ethernet (PoE) *	×	
J		Operational conditions		
10G support *	×	Operating temperature (T-T)	0 - 40 °C	
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-	Storage temperature (T-T)	-40 - 70 °C	
Full duplex	1	Operating relative humidity (H-H)	10 - 95%	
Flow control support	7	Storage relative humidity (H-H)	10 - 95%	
Broadcast storm control	1	Heat dissipation	16.03 BTU/h	
Rate limiting	✓	Weight & dimensions		
Auto MDI/MDI-X	✓	Width	250 mm	
VLAN support	✓	Depth	104 mm	
Number of VLANs	8	Height Weight	27 mm 620 g	
Data transmission		3	020 g	
Switching capacity *	16 Gbit/s	Packaging data		
		Calaba da da da d	A.C.	
Forwarding rate	11.9 Mpps	Cables included Quick start guide	AC ✓	

Data transmission		Packaging data		
MAC address table * Jumbo frames support Jumbo frames Packet buffer memory	8000 entries ✓ 9000 0.5 MB	User guide Manual Package type Package width	✓ ✓ Box 302 mm	
Security IGMP snooping MAC address filtering SSH/SSL support	<i>I I I</i>	Package depth Package height Package weight	227 mm 64 mm 1.1 kg	
Multicast features Multicast support	1			

