## Logitech Rally Bar Mini + Tap IP video conferencing system Ethernet LAN



**Brand**: Logitech **Product code**: 991-000389


Product name: Rally Bar Mini + Tap IP

Rally Bar Mini + Tap IP

Logitech Rally Bar Mini + Tap IP. HD type: 4K Ultra HD, Supported video modes: 576p, 720p, 900p, 1440p, 2160p, Maximum frame rate: 30 fps. Digital zoom: 4x. Ethernet LAN, Wi-Fi. Display: IPS, Display diagonal: 25.6 cm (10.1"), Display resolution: 1280 x 800 pixels. Product colour: Graphite

Performance		Microphone	
Product colour * Pan range Tilt angle range PTZ control	Graphite -25 - 25° -15 - 15°	Microphone sensitivity Microphone frequency Microphone direction type Sound pressure level (max) Number of microphones	-36 dB 90 - 16000 Hz Omnidirectional 90 dB 6
Technical details	05176000	Features	
Harmonized System (HS) code	85176990	Telepresence *	×
Video  HD type * Supported video modes Maximum frame rate	4K Ultra HD 576p, 720p, 900p, 1440p, 2160p 30 fps	Motion sensor Cable lock slot Cable lock slot type	✓ ✓ Kensington
Audio		Logistics data	
Built-in speaker(s) Output level Line-out impedance Output voltage Total Harmonic	√ 92/99 dB 4 Ω	Master (outer) case gross weight Master (outer) case length Master (outer) case width Master (outer) case height	8.87 kg 808 mm 258 mm 302 mm
Distortion (THD)	2%	Battery	
Audio beamforming	<b>√</b>	Battery capacity	0.675 Wh
Noise reduction Echo cancellation	1	Computer system	
RMS rated power Microphone pick-up range	<b>√</b> 5 W nge 4.5 m	Windows operating systems supported	Windows 10, Windows 11
Sample rates	0 - 48 kHz	Mac operating systems supported	Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey
Ports & interfaces		Operational conditions	
HDMI ports quantity HDMI output ports quantity HDMI input ports quantity USB connector type	3 2 1 USB Type-A, USB Type-C	Operating temperature (T-T) Operating relative humidity (H-H) Storage temperature (T-T) Heat dissipation	0 - 40 °C 10 - 95% -40 - 70 °C 64 BTU/h
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	3	Power	
Ethernet LAN (RJ-45) ports DC-in jack Microphone in	1 ✓ ✓	Power source type AC input voltage Current	AC 100 - 240 V 4.754 A
Interface module		DC input voltage Battery technology	19 V Lithium
Interface module RJ-45 ports quantity	1	Battery capacity Number of batteries supported	220 mAh
Network		Power plug type	Type G
Ethernet LAN * Ethernet LAN data rates Wi-Fi	10,100,1000 Mbit/s  802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac)	Weight & dimensions Interface module dimensions (W x D x H)	246.2 x 171.3 x 56.1 mm
Wi-Fi standards		Interface module weight	1 kg
upported network protocols IPv4, IPv6 ecurity algorithms 128-bit AES	Width Depth	719 mm 101 mm	

Camera		Weight & dimensions	
Zoom capability Digital zoom Horizontal field of view Vertical field of view Diagonal field of view Remote control interface	<ul><li>✓</li><li>4x</li><li>113°</li><li>80.7°</li><li>120°</li><li>Bluetooth</li></ul>	Height Weight Package width Package depth Package height Package weight	91.4 mm 4.03 kg 252 mm 802 mm 289 mm 8.87 kg
Display		Packaging content	
Display Display diagonal Display resolution Contrast ratio (typical) Touchscreen Touchscreen type Viewing angle, horizontal Viewing angle, vertical Display brightness Oleophobic coating	IPS 25.6 cm (10.1") 1280 x 800 pixels 1000:1  ✓ Capacitive 85° 85° 400 cd/m²  ✓	Cables included  Power cable length  HDMI cable length  AC adapter included  Mounting kit  Remote control included  Camera included  Quick start guide	AC, DC, HDMI, USB Type-A to USB Type-C 2.5 m 2 m



5099206102149

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.