

DELL Vostro 3710 Intel® Core™ i7 i7-12700 16 GB DDR4-SDRAM 512 GB SSD Windows 10 Pro SFF PC Black

Brand : DELL

Product family: Vostro

Product code: X5XHT

Product name : 3710

DELL Vostro 3710. Processor family: Intel® Core™ i7, Processor model: i7-12700. Internal memory: 16 GB, Internal memory type: DDR4-SDRAM, Memory clock speed: 3200 MHz. Total storage capacity: 512 GB, Storage media: SSD, Optical drive type: DVD±RW. On-board graphics card model: Intel UHD Graphics 770. Operating system installed: Windows 10 Pro, Operating system architecture: 64-bit. Power supply: 180 W. Chassis type: SFF. Product type: PC. Product colour: Black







Processor		Expansion slots	
Processor generation 12th ge	Intel® Core™ i7 12th gen Intel® Core™ i7	PCI Express x1 (Gen 3.x) slots PCI Express x16 slots PCI Express x16 (Gen 3.x) slots	1 1 1
Processor model * Processor cores Efficient-core base frequency Processor boost frequency Processor cache Bus type	i7-12700 12 1.6 GHz 4.9 GHz 25 MB DMI4 1 1	Design Chassis type * Placement supported Water cooling system Cable lock slot Product colour *	SFF Vertical ★ ✓ Black
Number of processors installed Number of processors supported		Performance	
Memory Internal memory * Maximum internal memory * Internal memory type Memory layout (slots x size) Memory slots	16 GB 64 GB DDR4-SDRAM 1 x 16 GB 2x DIMM	Market positioning Motherboard chipset Audio system Built-in speaker(s) Trusted Platform Module (TPM) Product type *	Business Intel B660 High Definition Audio X V PC
Memory clock speed	3200 MHz	Software	
Memory channels Storage Total storage capacity * Storage media * Optical drive type *	Dual-channel 512 GB SSD DVD±RW	Operating system installed * Operating system architecture Windows 11 free upgrade Operating system language	Windows 10 Pro 64-bit ✔ Multilingual

Storago		Softwara	
Storage	-	Software	
Number of storage drives installed Total SSDs capacity Number of SSDs installed	1 512 GB 1	Trial software	McAfee® Business Protection 30- day Trial, No Microsoft Office License Included 30 day Trial Offer Only
SSD capacity	512 GB	Processor special features	
SSD interface	NVMe, PCI Express	Intel 64	✓
NVMe	<	Enhanced Intel SpeedStep	4
SSD form factor	M.2	Technology Embedded options available	×
Card reader integrated Compatible memory cards	X	Intel VT-x with Extended Page	
RAID support	Not supported	Tables (EPT)	v
Graphics	~	Idle States	4
	<u> </u>	Intel Stable Image Platform Program (SIPP)	1
Discrete graphics card * On-board graphics card *	×	Intel Trusted Execution Technology	1
Discrete graphics card model *	Not available	Execute Disable Bit	1
On-board GPU manufacturer	Intel	CPU configuration (max)	1
On-board graphics card model * Maximum on-board graphics card	Intel UHD Graphics 770	Intel Virtualization Technology for Directed I/O (VT-d)	<
resolution	7680 x 4320 pixels	Intel Virtualization Technology (VT- x)	✓
Network		Power	
Ethernet LAN *		Power supply *	180 W
Ethernet LAN data rates	10,1000,100 Mbit/s	Power supply input voltage	90 - 264 V
Cabling technology Wi-Fi *	10/100/1000Base-T(X)	Power supply input frequency	47 - 63 Hz
Top Wi-Fi standard	Wi-Fi 5 (802.11ac)	Operational conditions	
Wi-Fi standards	Wi-Fi 5 (802.11ac)	Operating temperature (T-T)	10 - 35 °C
Wi-Fi standards WLAN controller manufacturer	Wi-Fi 5 (802.11ac) Realtek	Operating temperature (T-T) Storage temperature (T-T)	10 - 35 °C -40 - 65 °C
			-40 - 65 °C 20 - 80%
WLAN controller manufacturer WLAN controller model Antenna type	Realtek Realtek RTL8821CE 1x1	Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	-40 - 65 °C 20 - 80% 5 - 95%
WLAN controller manufacturer WLAN controller model	Realtek Realtek RTL8821CE	Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude	-40 - 65 °C 20 - 80% 5 - 95% -15.2 - 3048 m
WLAN controller manufacturer WLAN controller model Antenna type	Realtek Realtek RTL8821CE 1x1	Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude	-40 - 65 °C 20 - 80% 5 - 95% -15.2 - 3048 m -15.2 - 10668 m
WLAN controller manufacturer WLAN controller model Antenna type Bluetooth	Realtek Realtek RTL8821CE 1x1	Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Operating vibration	-40 - 65 °C 20 - 80% 5 - 95% -15.2 - 3048 m -15.2 - 10668 m 0.26 G
WLAN controller manufacturer WLAN controller model Antenna type Bluetooth Ports & interfaces USB 2.0 ports quantity * USB 3.2 Gen 1 (3.1 Gen 1) Type-A	Realtek Realtek RTL8821CE 1x1 ✓	Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Operating vibration Non-operating vibration	-40 - 65 °C 20 - 80% 5 - 95% -15.2 - 3048 m -15.2 - 10668 m
WLAN controller manufacturer WLAN controller model Antenna type Bluetooth Ports & interfaces USB 2.0 ports quantity * USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity *	Realtek Realtek RTL8821CE 1x1 ✓ 4 4	Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Operating vibration	-40 - 65 °C 20 - 80% 5 - 95% -15.2 - 3048 m -15.2 - 10668 m 0.26 G 1.37 G
WLAN controller manufacturer WLAN controller model Antenna type Bluetooth Ports & interfaces USB 2.0 ports quantity * USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity * HDMI ports quantity *	Realtek Realtek RTL8821CE 1x1 ✓ 4 4 1	Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Operating vibration Non-operating vibration Operating shock Non-operating shock	-40 - 65 °C 20 - 80% 5 - 95% -15.2 - 3048 m -15.2 - 10668 m 0.26 G 1.37 G 40 G
WLAN controller manufacturer WLAN controller model Antenna type Bluetooth Ports & interfaces USB 2.0 ports quantity * USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity *	Realtek Realtek RTL8821CE 1x1 ✓ 4 4	Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Operating vibration Non-operating vibration Operating shock Non-operating shock Weight & dimensions	-40 - 65 °C 20 - 80% 5 - 95% -15.2 - 3048 m -15.2 - 10668 m 0.26 G 1.37 G 40 G 105 G
WLAN controller manufacturer WLAN controller model Antenna type Bluetooth Ports & interfaces USB 2.0 ports quantity * USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity * HDMI ports quantity *	Realtek Realtek RTL8821CE 1x1 ✓ 4 4 1 1.4b	Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Operating vibration Non-operating vibration Operating shock Non-operating shock Weight & dimensions Width *	-40 - 65 °C 20 - 80% 5 - 95% -15.2 - 3048 m -15.2 - 10668 m 0.26 G 1.37 G 40 G 105 G 92.6 mm
 WLAN controller manufacturer WLAN controller model Antenna type Bluetooth Ports & interfaces USB 2.0 ports quantity * USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity * HDMI ports quantity * HDMI version DisplayPorts quantity 	Realtek Realtek RTL8821CE 1x1 ✓ 4 4 1 1.4b 1	Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Operating vibration Non-operating vibration Operating shock Non-operating shock Weight & dimensions	-40 - 65 °C 20 - 80% 5 - 95% -15.2 - 3048 m -15.2 - 10668 m 0.26 G 1.37 G 40 G 105 G
 WLAN controller manufacturer WLAN controller model Antenna type Bluetooth Ports & interfaces USB 2.0 ports quantity * USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity * HDMI ports quantity * HDMI version DisplayPorts quantity DisplayPort version Ethernet LAN (RJ-45) ports Line-out 	Realtek Realtek RTL8821CE 1x1 ✓ 4 4 1 1.4b 1 1.4a	Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Operating vibration Non-operating vibration Operating shock Non-operating shock Weight & dimensions Width * Depth *	-40 - 65 °C 20 - 80% 5 - 95% -15.2 - 3048 m -15.2 - 10668 m 0.26 G 1.37 G 40 G 105 G 92.6 mm 292.8 mm
 WLAN controller manufacturer WLAN controller model Antenna type Bluetooth Ports & interfaces USB 2.0 ports quantity * USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity * HDMI ports quantity * HDMI version DisplayPorts quantity DisplayPort version Ethernet LAN (RJ-45) ports Line-out Combo headphone/mic port 	Realtek Realtek RTL8821CE 1x1 ✓ 4 4 1 1.4b 1 1.4b 1 1.4a 1 ↓	Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Operating vibration Operating vibration Operating shock Non-operating shock Weight & dimensions Width * Depth * Height * Weight *	-40 - 65 °C 20 - 80% 5 - 95% -15.2 - 3048 m -15.2 - 10668 m 0.26 G 1.37 G 40 G 105 G 92.6 mm 292.8 mm 290 mm
 WLAN controller manufacturer WLAN controller model Antenna type Bluetooth Ports & interfaces USB 2.0 ports quantity * USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity * HDMI ports quantity * HDMI version DisplayPorts quantity Ethernet LAN (RJ-45) ports Line-out Combo headphone/mic port Number of rear USB ports 	Realtek Realtek RTL8821CE 1x1 ✓ 4 4 1 1.4b 1 1.4b 1 1.4a 1 ↓ ✓ ↓ 4	Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Operating vibration Operating vibration Operating shock Non-operating shock Non-operating shock Weight & dimensions Width * Depth * Height * Weight * Weight *	-40 - 65 °C 20 - 80% 5 - 95% -15.2 - 3048 m -15.2 - 10668 m 0.26 G 1.37 G 40 G 105 G 92.6 mm 292.8 mm 290 mm 4.52 kg
 WLAN controller manufacturer WLAN controller model Antenna type Bluetooth Ports & interfaces USB 2.0 ports quantity * USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity * HDMI ports quantity * HDMI version DisplayPorts quantity Ethernet LAN (RJ-45) ports Line-out Combo headphone/mic port Number of rear USB ports Number of front USB ports 	Realtek Realtek RTL8821CE 1x1 ✓ 4 4 1 1.4b 1 1.4a 1 ↓ ✓ ✓ ↓ 4	Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Operating altitude Operating vibration Non-operating vibration Operating shock Non-operating shock Non-operating shock Weight & dimensions Width * Depth * Height * Height * Packaging content Display included *	-40 - 65 °C 20 - 80% 5 - 95% -15.2 - 3048 m -15.2 - 10668 m 0.26 G 1.37 G 40 G 105 G 92.6 mm 292.8 mm 290 mm 4.52 kg
 WLAN controller manufacturer WLAN controller model Bluetooth Ports & interfaces VSB 2.0 ports quantity * USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity * HDMI ports quantity * HDMI ports quantity * HDMI version DisplayPorts quantity Ethernet LAN (RJ-45) ports Line-out Combo headphone/mic port Number of rear USB ports Number of front uSB ports Number of front audio ports 	Realtek Realtek RTL8821CE 1x1 ✓ 4 4 1 1.4b 1 1.4a 1 ↓ ✓ ↓ ↓ 4 4 4 1	Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Operating vibration Operating vibration Operating shock Non-operating shock Non-operating shock Weight & dimensions Width * Depth * Height * Weight * Weight *	-40 - 65 °C 20 - 80% 5 - 95% -15.2 - 3048 m -15.2 - 10668 m 0.26 G 1.37 G 40 G 105 G 92.6 mm 292.8 mm 290 mm 4.52 kg
 WLAN controller manufacturer WLAN controller model Antenna type Bluetooth Ports & interfaces USB 2.0 ports quantity * USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity * HDMI ports quantity * HDMI ports quantity * HDMI version DisplayPorts quantity DisplayPort version Ethernet LAN (RJ-45) ports Line-out Combo headphone/mic port Number of rear USB ports Number of front audio ports Number of rear audio ports 	Realtek Realtek RTL8821CE 1x1 ✓ 4 4 1 1.4b 1 1.4a 1 ↓ ✓ ✓ ↓ 4	Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Operating vibration Non-operating vibration Operating shock Non-operating shock Weight & dimensions Width * Depth * Height * Weight * Packaging content Display included * Mouse included on selected markets only Mouse connectivity	-40 - 65 °C 20 - 80% 5 - 95% -15.2 - 3048 m -15.2 - 10668 m 0.26 G 1.37 G 40 G 105 G 92.6 mm 292.8 mm 290 mm 4.52 kg
 WLAN controller manufacturer WLAN controller model Bluetooth Ports & interfaces VSB 2.0 ports quantity * USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity * HDMI ports quantity * HDMI ports quantity * HDMI version DisplayPorts quantity Ethernet LAN (RJ-45) ports Line-out Combo headphone/mic port Number of rear USB ports Number of front uSB ports Number of front audio ports 	Realtek Realtek RTL8821CE 1x1 ✓ 4 4 1 1.4b 1 1.4a 1 ↓ ✓ ↓ ↓ 4 4 4 1	Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Operating vibration Non-operating vibration Operating shock Non-operating shock Non-operating shock Weight & dimensions Width * Depth * Height * Weight * Packaging content Display included * Mouse included on selected markets only	-40 - 65 °C 20 - 80% 5 - 95% -15.2 - 3048 m -15.2 - 10668 m 0.26 G 1.37 G 40 G 105 G 92.6 mm 292.8 mm 290 mm 4.52 kg
WLAN controller manufacturer WLAN controller model Antenna type Bluetooth Ports & interfaces USB 2.0 ports quantity * USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity * HDMI ports quantity * HDMI version DisplayPorts quantity Ethernet LAN (RJ-45) ports Line-out Combo headphone/mic port Number of front USB ports Number of front audio ports Number of rear audio ports Number of rear audio ports	Realtek Realtek RTL8821CE 1x1 ✓ 4 4 4 1 1.4b 1 1.4a 1 ✓ ✓ 4 4 4 1 1	Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Operating vibration Non-operating vibration Operating shock Non-operating shock Weight & dimensions Width * Depth * Height * Weight * Packaging content Display included * Mouse included on selected markets only Mouse connectivity Keyboard included on selected	-40 - 65 °C 20 - 80% 5 - 95% -15.2 - 3048 m -15.2 - 10668 m 0.26 G 1.37 G 40 G 105 G 92.6 mm 292.8 mm 290 mm 4.52 kg

Cables included

AC



5397184732373

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.