PHILIPS

Philips 75BDL3052E/00 Signage Display 190.5 cm (75") LCD 350 cd/m² 4K Ultra HD Black Touchscreen Android 8.0

Brand : Philips Product code: 75BDL3052E/00

Product name: 75BDL3052E/00

75" (3840x2160), 350cd/m², 16:9, Android 8.0, 400W, 100-240V, 55.77kg Philips 75BDL3052E/00. Display diagonal: 190.5 cm (75"), Display technology: LCD, Display resolution: 3840 x 2160 pixels, Display brightness: 350 cd/m², HD type: 4K Ultra HD, Touchscreen. Operating system installed: Android 8.0. Product colour: Black





Display diagonal * 190.5 cm (75*)				
Display technology CD Display resolution 3840 x 2160 pixels Number of OSD languages 18 Arabic, Danish, German, Dutch, English, Spanish, Finnish, French, 170 touchscreen 4 Ultra HD On Screen Display (OSD) languages Regilsh, Spanish, Finnish, French, 170 touchscreen 16:9	Display		Design	
Display resolution 3840 x 2160 pixels		` '	Anti-glare screen	✓
Number of OSD languages 18			Performance	
HD type *	' '	•	Number of OSD languages	18
Response time 8 ms Contrast ratio (typical) 1200:1 Mean time between failures (MTBF) 50000 h Viewing angle, horizontal 178° Power Viewing angle, vertical 178° Power consumption (typical) 155 W Display number of colours 1.07 billion colours Power consumption (standby) 0.5 W Display number of colours 1.09 x 0.4296 mm Energy efficiency class (HDR) G Display diagonal (metric) 189.3 cm Ac input voltage 100 - 240 V Native refresh rate 60 Hz AC input frequency 50 - 60 Hz Ports & interfaces Power consumption (standby) 100 - 240 V Ac input oftage 100 - 240 V Ac input frequency 50 - 60 Hz Ports & interfaces Computer system HDMI ports quantity 3 Internal memory 3 GB DVI port 4	HD type *	4K Ultra HD	On Screen Display (OSD) languages	English, Spanish, Finnish, French, Italian, Norwegian, Polish,
Response time 8 ms Contrast ratio (typical) 1200-1 Viewing angle, horizontal 178° Power Viewing angle, vertical 178° Power consumption (typical) * 155 W Display number of colours 1.07 billion colours Power consumption (standby) * 0.5 W Pikel pitch 0.4296 x 0.4296 mm Energy efficiency class (HDR) G Display diagonal (metric) 189.3 cm AC input voltage 100 - 240 V Native refresh rate 60 Hz AC input frequency 50 - 60 Hz Ports & interfaces HDMI ports quantity 3 Internal memory 3 GB HDMI version 2.0 Internal memory 16 GB DVI port * ✓ Operating system installed Android 8.0 DVI-D ports quantity 11 Video formats supported MPEG21, MPEG4, MPS USB ports quantity 4 4 Walled formats supported MPEG21, MPEG4, MPS USB ports quantity 4 4 Weight & dimensions Ethernet LAN * ✓ Weight & dimensions Ethernet LAN * ✓ Display width 1715.5 mm Ethernet LAN (R)-45) ports 1 Display height 1001.5 mm Remote (IR) input 1 Display height 1001.5 mm Pockage weight 67.6 kg Audio Built-in speakers 2 Ack Peakaging data Packaging content Number of built-in speakers 2 Cables included Ack, DVI, HDMI, IR sensor, USB Type-RMS rated power 30 Weight (IR-M) Pocacement supported Ack, DVI, HDMI, IR sensor, USB Type-RMS rated power 50 Storage temperature (T-T) 0 - 40 °C Operating relative humidity (H-H) 5 - 95% VESA mounting * VESA Mounting + VESA Mounting the Mounting the Municipus Humidity (H-H) 5 - 95%	Native aspect ratio	16:9		3
Contrast ratio (typical) 178° Power	•		Mean time between failures (MTBF)	
Viewing angle, vertical Display number of colours Display number of colours Display number of colours Display diagonal (metric) 189.3 cm AC input voltage NAC input frequency SO - 60 Hz Computer system Internal memory SA GB NAC input voltage NAC input voltage NAC input voltage NAC input frequency SO - 60 Hz Computer system Internal memory SA GB NAC input system installed NAC input voltage NAC input system installed NAC input	- · ·			
Display number of colours Pixel pitch 0.4296 x 0.4296 mm 0.4296 x 0.4296 mm 0.4296 x 0.4296 mm 0.51939 diagonal (metric) 189.3 cm 0.60 Hz 1.00 Hz 1.0				1EE W
Pixel pitch 0.4296 x 0.4296 mm Energy efficiency class (HDR) G Display diagonal (metric) 189.3 cm AC input voltage 100 - 240 V Native refresh rate 60 Hz AC input voltage 100 - 240 V Ports & interfaces Computer system HDMI ports quantity * 3 Internal storage capacity 16 GB DVI port * ✓ Operating system installed Android 8.0 DVI-D ports quantity 1 Video formats supported H.263, H.264, H.265, MPEG, MPEG				
Display diagonal (metric) 189.3 cm AC input voltage 50 - 240 V Native refresh rate 60 Hz AC input frequency 50 - 60 Hz Ports & interfaces HDMI ports quantity* 3 Internal memory 3 GB HDMI version 2.0 Internal storage capacity 16 GB DVI port* V Operating system installed Android 8.0 DVI-D ports quantity 1 Video formats supported MEGG1, MPEG4, VP9 USB port* V USB port* V USB port quantity 4 Image formats supported AAC, HE-AAC USB ports quantity 4 Image formats supported BMP, JPEG, PNG USB version 2.0 Weight & dimensions Ethernet LAN* V Ethernet LAN (RJ-45) ports 1 Display width 1715.5 mm Ethernet LAN (RJ-45) ports 1 Display weight 100.5 mm Remote (IR) input 1 Display weight 101.5 mm Remote (IR) output 1 Display weight 55.8 kg DC-in jack V OPS module slot V Audio Built-in speaker(s)* V Number of built-in speakers 2 Cables included AC, DVI, HDMI, IR sensor, USB Type-RMS rated power 30 W Design Design Indoor Operating temperature (T-T) 0 - 40 °C Product colour * Operating relative humidity (H-H) 20 - 80% Storage relative humidity (H-H) 20 - 80%	• •			
Native refresh rate 60 Hz AC input frequency 50 - 60 Hz Ports & interfaces HDMI ports quantity 3 3 Internal memory 3 GB HDMI version 2.0 Internal storage capacity 16 GB DVI port 4	·		• • • • • • • • • • • • • • • • • • • •	
Ports & interfaces Computer system HDMI ports quantity* 3 Internal memory 3 GB HDMI version 2.0 Internal storage capacity 16 GB DVI port * ✓ Operating system installed Android 8.0 DVI-D ports quantity 1 Video formats supported H.263, H.264, H.265, MPEG, MPEG, MPEG, MPEGA, VP9 USB port * ✓ Audio formats supported AAC, HE-AAC USB ports quantity 4 Image formats supported BMP, JPEG, PNG USB version 2.0 Weight & dimensions Ethernet LAN (R)-45) ports 1 Display width 1715.5 mm Ethernet LAN (R)-45) ports 1 Display depth 1007.6 mm Remote (IR) input 1 Display height 1007.6 mm Remote (IR) output 1 Display weight 55.8 kg DC-in jack ✓ Packaging data OPS module slot ✓ Packaging content Audio V Packaging content Built-in speaker(s) * ✓ Cables included AC, DVI, HDMI, IR sensor, USB Type-A to Micro USB-B RMS rated power 30 W Operating temperature (T-T) 0 - 40 °C Operating relative humidity (H-H) 2-0.60 °C <			·	
HDMI ports quantity * 3 Internal memory 3 GB HDMI version 2.0 Internal storage capacity 16 GB DVI port *			,	
HDMI version 2.0 Internal storage capacity 16 GB DVI port *	HDMI ports quantity *	3		3 GB
DVI port *	' ' '		•	
Video formats supported MPEG21, MPEG4, VP9 USB port *		√		Android 8.0
Audio formats supported AAC, HE-AAC USB port * USB port squantity 4 USB ports quantity 6 USB ports quantity 6 USB ports quantity 6 USB ports quantity 8 USB ports quantity 9 USL		=	Video formats supported	
USB ports quantity 4 Image formats supported BMP, JPEG, PNG USB version 2.0 Weight & dimensions Ethernet LAN * / Display width 1715.5 mm Ethernet LAN (RJ-45) ports 1 Display width 1007.6 mm Remote (IR) input 1 Display height 1007.6 mm Remote (IR) output 1 Display weight 55.8 kg DC-in jack / DC-in jack / Packaging data OPS module slot / Package weight 67.6 kg Built-in speaker(s) * / Packaging content Number of built-in speakers 2 Cables included AC, DVI, HDMI, IR sensor, USB Type-A to Micro USB-B Mackaging conditions Design			Audio formats supported	
USB version 2.0 Weight & dimensions Ethernet LAN* V Display width 1715.5 mm Ethernet LAN (RJ-45) ports 1 Display depth 101.5 mm Remote (IR) input 1 Display height 1007.6 mm Remote (IR) output 1 Display weight 55.8 kg DC-in jack V Packaging data OPS module slot V Package weight 67.6 kg Built-in speaker(s)* V Packaging content Number of built-in speakers 2 Cables included AC, DVI, HDMI, IR sensor, USB Type-A to Micro USB-B RMS rated power 30 W Operating temperature (T-T) 0 - 40 °C Operating relative humidity (H-H) 20 - 80% Storage relative humidity (H-H) 5 - 95%		*	""	,
Ethernet LAN *		•		,, -,
Ethernet LAN (RJ-45) ports 1 Display depth 101.5 mm Remote (IR) input 1 1 Display height 1007.6 mm Remote (IR) output 1 1 Display height 55.8 kg DC-in jack			•	1715 5 mm
Remote (IR) input 1 Display height 1007.6 mm Remote (IR) output 1 Display height 55.8 kg DC-in jack	Ethernet LAN (RJ-45) ports	1		
Remote (IR) output DC-in jack OPS module slot Audio Built-in speaker(s) * Number of built-in speakers RMS rated power Placement supported * Product colour * VESA mounting * Display weight Packaging data Package weight Packaging content Cables included AC, DVI, HDMI, IR sensor, USB Type-A to Micro USB-B Operational conditions Operating temperature (T-T) Operating relative humidity (H-H) Storage temperature (T-T) Storage relative humidity (H-H) S - 95%	• •	1	, , ,	
DC-in jack OPS module slot Audio Built-in speaker(s) * Number of built-in speakers RMS rated power Packaging content Cables included Operational conditions Placement supported * Product colour * VESA mounting * Audio Packaging data Package weight Packaging content Cables included AC, DVI, HDMI, IR sensor, USB Type-A to Micro USB-B Operational conditions Operating temperature (T-T) Operating relative humidity (H-H) Operating relative humidity (H-H) Storage relative humidity (H-H) Storage relative humidity (H-H) Storage relative humidity (H-H) Design Operating relative humidity (H-H) Storage relative humidity (H-H) Storage relative humidity (H-H) Operating temperature (T-T) Storage relative humidity (H-H) Storage relative humidity (H-H)	Remote (IR) output	1	. , ,	
Audio Built-in speaker(s) * Number of built-in speakers RMS rated power Packaging content Cables included AC, DVI, HDMI, IR sensor, USB Type-A to Micro USB-B Cables included Operational conditions Operating temperature (T-T) Product colour * VESA mounting * Operating relative humidity (H-H) Storage relative humidity (H-H)	DC-in jack	✓		33.0 kg
Audio Built-in speaker(s) * Number of built-in speakers RMS rated power Packaging content Cables included AC, DVI, HDMI, IR sensor, USB Type-A to Micro USB-B Operational conditions Operating temperature (T-T) Product colour * VESA mounting * Operating temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	OPS module slot	✓		67.61
Number of built-in speakers RMS rated power 2 Cables included AC, DVI, HDMI, IR sensor, USB Type-A to Micro USB-B Operational conditions Operating temperature (T-T) Placement supported * Product colour * VESA mounting * AC, DVI, HDMI, IR sensor, USB Type-A to Micro USB-B Operating temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) 5 - 95%	Audio		3 3	67.6 Kg
RMS rated power 30 W Placement supported * Indoor Product colour * Black VESA mounting * A to Micro USB-B A to Micro USB-B A to Micro USB-B A to Micro USB-B Operational conditions Operating temperature (T-T) 0 - 40 °C Operating relative humidity (H-H) 20 - 80% Storage temperature (T-T) -20 - 60 °C Storage relative humidity (H-H) 5 - 95%	Built-in speaker(s) *	✓	Packaging content	
RMS rated power Placement supported * Indoor Product colour * Black VESA mounting * Operational conditions Operating temperature (T-T) 0 - 40 °C Operating relative humidity (H-H) 20 - 80% Storage temperature (T-T) -20 - 60 °C Storage relative humidity (H-H) 5 - 95%	Number of built-in speakers	2	Cables included	AC, DVI, HDMI, IR sensor, USB Type-
Placement supported * Indoor Product colour * Black VESA mounting * Operating temperature (T-T) 0 - 40 °C Operating relative humidity (H-H) 20 - 80% Storage temperature (T-T) -20 - 60 °C Storage relative humidity (H-H) 5 - 95%	RMS rated power	30 W		A LU MILLU USD-D
Placement supported * Indoor Operating relative humidity (H-H) 20 - 80% Product colour * Black VESA mounting * ✓ Storage relative humidity (H-H) 5 - 95%	Design			0.40.00
Product colour * Black VESA mounting * VESA mounting * Storage temperature (T-T) -20 - 60 °C Storage relative humidity (H-H) 5 - 95%	Placement supported *	Indoor		
VESA mounting * Storage relative humidity (H-H) 5 - 95%	Product colour *	Black		
Panel mounting interface 600 x 400 mm Storage relative numidity (H-H) 5 - 95%	VESA mounting *	✓	• •	
	Panel mounting interface	600 x 400 mm	Storage relative numidity (H-H)	o - 95%

Technical details

Sustainability certificates

CE, Federal Communications Commission (FCC), RoHS





8712581785307

0685417588183



685417588183

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.