

ZYXEL

## Zyxel WX3100-T0-EU01V2F wireless access point 1200 Mbit/s White

**Brand :** Zyxel

**Product code:** WX3100-T0-EU01V2F

**Product name :** WX3100-T0-EU01V2F

- WiFi 6 (11ax) for superior performance and coverage
- Video-grade QoS for optimized video streaming
- Zyxel-developed OPAL for superior flexibility and faster time-to-market
- Zyxel MPro Mesh® Solutions (compliant with EasyMesh s
- Remote management via TR-069 and TR-181 i2 tandards)
- Integrated beamforming technology
- Dual images for reliable system recovery

Wifi 6 AX1800 Dual Band Gigabit Access Point/Extender with Easy Mesh Support

Zyxel WX3100-T0-EU01V2F. Maximum data transfer rate: 1200 Mbit/s, Maximum data transfer rate (2.4 GHz): 600 Mbit/s, Maximum data transfer rate (5 GHz): 1200 Mbit/s. Security algorithms: WMM, WPA2, WPA2-PSK, WPA3-SAE. DC voltage range: 12 V, Input current: 1 A. Product colour: White. Antenna type: Internal



Features		Power	
2.4 GHz *	✓	Input current	1 A
5 GHz *	✓	<b>Design</b>	
6 GHz *	✗	Product colour *	White
Maximum data transfer rate *	1200 Mbit/s	On/off switch	✓
Maximum data transfer rate (2.4 GHz)	600 Mbit/s	Reset button	✓
Maximum data transfer rate (5 GHz)	1200 Mbit/s	WPS push button	✓
Ethernet LAN data rates	10,100,1000 Mbit/s	LED indicators	✓
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n	<b>Antenna</b>	
MIMO	✓	Antenna type *	Internal
MIMO type	Multi User MIMO	<b>Weight &amp; dimensions</b>	
Wi-Fi Multimedia (WMM)/(WME)	✓	Width	128 mm
VLAN support	✓	Depth	40 mm
<b>Security</b>		Height	128 mm
Security algorithms *	WMM, WPA2, WPA2-PSK, WPA3-SAE	Weight	314 g
IGMP snooping	✓	<b>Packaging data</b>	
<b>Protocols</b>		Package width	279 mm
DHCP client	✓	Package depth	137 mm
<b>Management features</b>		Package height	44 mm
Web-based management	✓	Package weight	532 g
<b>Ports &amp; interfaces</b>		<b>Operational conditions</b>	
Ethernet LAN (RJ-45) ports *	2	Operating relative humidity (H-H)	10 - 90%
DC-in jack	✓	Operating temperature (T-T)	0 - 40 °C
<b>Power</b>		Storage temperature (T-T)	-30 - 70 °C
DC voltage range	12 V	Storage relative humidity (H-H)	10 - 95%



4718937616848

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 29-APR-2024. Prints or copies of Information are only valid on the printed Publication date