ZYXEL

Zyxel GS1900-8HP v3 PoE Managed L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Black

Brand : Zyxel **Product code:** GS1900-8HP-GB0103F

Product name: GS1900-8HP v3 PoE

 $8~ports,\,10/100/1000Base-T$ PoE, MAC8K, IEEE 802.1D STP / 802.1w RSTP / 802.1s MSTP, L2 Multicast, PoE, GB

Zyxel GS1900-8HP v3 PoE. Switch type: Managed, Switch layer: L2. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 8. Full duplex. MAC address table: 8000 entries, Switching capacity: 16 Gbit/s. Networking standards: IEEE 802.1Q, IEEE 802.1p, IEEE 802.1x, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3af, IEEE.... Power connector: DC-in jack. Power over Ethernet (PoE)






Management features		Multicast features				
Switch type *	Managed L2	Multicast support ✓				
Switch layer		Design				
Quality of Service (QoS) support	√	Product colour	Black			
Web-based management	1	Reset button	✓			
Ports & interfaces		Certification	CE, FCC, C-Tick, RoHS			
Basic switching RJ-45 Ethernet ports quantity *	8	Performance				
Basic switching RJ-45 Ethernet ports	Gigabit Ethernet (10/100/1000)	Mean time between failures (MTBF)	533086 h			
type *	-	Power				
Power connector	DC-in jack	Power source *	AC/DC			
Network		AC input voltage	100 - 240 V			
Networking standards *	IEEE 802.1Q, IEEE 802.1p, IEEE 802.1x, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3af, IEEE 802.3at, IEEE 80	AC input frequency	50 - 60 Hz			
		Power consumption (typical)	90 W			
		Power over Ethernet (PoE)				
Full duplex	IEEE 802.3x	Power over Ethernet (PoE) *	✓			
Flow control support	,	Power over Ethernet (PoE) ports	8			
Broadcast storm control	1	quantity Total Power over Ethernet (PoE)	70 W			
Rate limiting	1	budget				
Auto MDI/MDI-X	1	Operational conditions				
VLAN support	✓	Operating relative humidity (H-H)	10 - 90%			
Data transmission		Weight & dimensions				
Switching capacity *	16 Gbit/s	Width	250 mm			
MAC address table *	8000 entries	Depth	104 mm			
Number of queues	8	Height	27 mm			
Jumbo frames support	√ 9216	Weight	710 g			
Jumbo frames	3210	Logistics data				
Security		Harmonized System (HS) code	85176990			
DHCP features	DHCP client	Trainformed System (115) code 05170550				
IGMP snooping	√					
Security algorithms	802.1x RADIUS					

_						
5	Δ	r	п	r	it	v

MAC address filtering



4718937621286

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.